

## Safety Data Sheet

## Firestone Building Products Company

## Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

## 1.1 Product identifier

**Product Name** • Quick Dual Part 2

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified use(s)** • One component of a two-component polyurethane system

## 1.3 Details of the supplier of the safety data sheet

**Manufacturer** • Firestone Building Products Company  
200 4th Avenue S  
Nashville, TN 37201-2208  
United States

genflexmsds@bfdp.com

**Telephone (General)** • 800-428-4442

## 1.4 Emergency telephone number

**Manufacturer** • (800) 424-9300 - CHEMTREC

**Manufacturer** • (703) 527-3887 - CHEMTREC - International

## Section 2: Hazards Identification

## EU/EEC

According to: Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 2015/830]

## 2.1 Classification of the substance or mixture

**CLP** • Compressed Gas - H280  
Specific Target Organ Toxicity Repeated Exposure 2 - H373

## 2.2 Label Elements

**CLP**

**WARNING**

**Hazard statements** • H280 - Contains gas under pressure; may explode if heated

**Precautionary statements**

**Prevention** • P260 - Do not breathe mist, vapours and/or spray.

**Response** • P314 - Get medical advice/attention if you feel unwell.

**Storage/Disposal** • P410+P403 - Protect from sunlight. Store in a well-ventilated place.  
P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## 2.3 Other Hazards

- CLP**
- This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces.  
According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

## United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

### 2.1 Classification of the substance or mixture

- OSHA HCS 2012**
- Compressed Gas  
Eye Mild Irritation 2B  
Specific Target Organ Toxicity Repeated Exposure 2  
Simple Asphyxiant

### 2.2 Label elements

**OSHA HCS 2012**

#### WARNING



- Hazard statements**
- Contains gas under pressure; may explode if heated  
Causes eye irritation  
May cause damage to organs - kidneys and/or gastrointestinal system through prolonged or repeated exposure  
May displace oxygen and cause rapid suffocation.

#### Precautionary statements

- Prevention**
- Wash thoroughly after handling.  
Do not breathe mist, vapours and/or spray.
- Response**
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
Get medical advice/attention if you feel unwell.
- Storage/Disposal**
- Protect from sunlight. Store in a well-ventilated place.  
Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## 2.3 Other hazards

- OSHA HCS 2012**
- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

## Canada

According to: WHMIS 2015

### 2.1 Classification of the substance or mixture

- WHMIS 2015**
- Compressed Gas  
Eye Mild Irritation 2B  
Specific Target Organ Toxicity Repeated Exposure 2  
Simple Asphyxiants 1

### 2.2 Label elements

**WHMIS 2015**

#### WARNING



- Hazard statements** • Contains gas under pressure; may explode if heated  
 Causes eye irritation  
 May cause damage to organs - kidneys and/or gastrointestinal system through prolonged or repeated exposure  
 May displace oxygen and cause rapid suffocation.

### Precautionary statements

- Prevention** • Wash thoroughly after handling.  
 Do not breathe mist, vapours and/or spray.
- Response** • IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical advice/attention.  
 Get medical advice/attention if you feel unwell.
- Storage/Disposal** • Protect from sunlight. Store in a well-ventilated place.  
 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

### 2.3 Other hazards

#### WHMIS 2015

- In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

## Section 3 - Composition/Information on Ingredients

### 3.1 Substances

- Material does not meet the criteria of a substance.

### 3.2 Mixtures

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
1,1,1,2-Tetrafluoroethane	CAS:811-97-2 EC Number:212-377-0	10% TO 15%	Inhalation-Rat LC50 • 1500 g/m <sup>3</sup> 4 Hour(s)	EU CLP: Press. Gas, H280 OSHA HCS 2012: Press. Gas; Simp. Asphyx. WHMIS 2015: Press. Gas; Simp. Asphyx.	NDA
Dipropylene Glycol	CAS:25265-71-8 EINECS:246-770-3	< 15%	Ingestion/Oral-Rat LD50 • 14850 mg/kg Skin-Rabbit LD50 • >20 mL/kg	EU CLP: Not Classified OSHA HCS 2012: Not Classified WHMIS 2015: Not Classified	NDA
Diethylene Glycol	CAS:111-46-6 EC Number:203-872-2 EU Index:603-140-00-6	< 15%	Skin-Rabbit LD50 • 11890 mg/kg Ingestion/Oral-Rat LD50 • 12000 mg/kg	EU CLP: Annex VI, Table 3.1: Acute Tox. 4, H302 OSHA HCS 2012: Eye Irrit. 2 WHMIS 2015: Eye Irrit. 2	NDA

See Section 16 for full text of H-statements.

## Section 4 - First Aid Measures

## 4.1 Description of first aid measures

- Inhalation**
- Move victim to fresh air. Give artificial respiration if victim is not breathing. Administer oxygen if breathing is difficult. Get medical attention immediately.
- Skin**
- Wash skin with soap and water. If irritation develops and persists, get medical attention.
- Eye**
- In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.
- Ingestion**
- Do NOT induce vomiting. If the subject is conscious, wash mouth and give 2 or more cups of milk or water. Never give anything by mouth to an unconscious person. Obtain medical attention immediately if ingested.

## 4.2 Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

## 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to Physician**
- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

## Section 5 - Firefighting Measures

### 5.1 Extinguishing media

- Suitable Extinguishing Media**
- Carbon dioxide, dry chemical, dry sand, foam, water spray.

- Unsuitable Extinguishing Media**
- Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

- Unusual Fire and Explosion Hazards**
- Containers may explode when heated. Ruptured cylinders may rocket.

- Hazardous Combustion Products**
- No data available

### 5.3 Advice for firefighters

- Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.  
Always wear thermal protective clothing when handling refrigerated/cryogenic liquids. Wear positive pressure self-contained breathing apparatus (SCBA).  
Move containers from fire area if you can do it without risk.  
FIRE: If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.  
FIRE INVOLVING TANKS: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.  
FIRE INVOLVING TANKS: Cool containers with flooding quantities of water until well after fire is out.  
FIRE INVOLVING TANKS: Do not direct water at source of leak or safety devices; icing may occur.  
FIRE INVOLVING TANKS: Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank.  
FIRE INVOLVING TANKS: ALWAYS stay away from tanks engulfed in fire.

## Section 6 - Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal Precautions**
- Ventilate the area before entry. Do not walk through spilled material. Use appropriate

Personal Protective Equipment (PPE) Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

## Emergency Procedures

- Keep unauthorized personnel away. Keep out of low areas. Stay upwind. **LARGE SPILL:** Consider initial downwind evacuation for at least 500 meters (1/3 mile) As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions.

## 6.2 Environmental precautions

- Prevent entry into waterways, sewers, basements or confined areas.

## 6.3 Methods and material for containment and cleaning up

### Containment/Clean-up Measures

- Stop leak if you can do it without risk.  
Allow substance to evaporate.  
Isolate area until gas has dispersed.  
If possible, turn leaking containers so that gas escapes rather than liquid.  
Use water spray to reduce vapors; do not put water directly on leak, spill area or inside container.  
Do not direct water at spill or source of leak.

## 6.4 Reference to other sections

- Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

## Section 7 - Handling and Storage

### 7.1 Precautions for safe handling

#### Handling

- Use only with adequate ventilation. Use good safety and industrial hygiene practices. When handling the product, avoid contact with eyes, skin, and clothing, using protective equipment as needed. Do not breathe mist, vapours and/or spray. Do not use this product around children, and secure it away from children. To prevent ingestion or contact following use of the product, wash hands and face before eating, drinking, applying cosmetics, or using tobacco. Remove contaminated clothing and protective equipment before entering eating/drinking areas. Containers should be kept tightly closed to prevent contact with moisture and other chemicals. Do not reuse empty containers for any purpose.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

- Keep containers tightly sealed during storage. Store in a dry, well-ventilated area away from sources of ignition and incompatible materials (see Section #10). Protect from heat and direct sunlight. Recommended temperature for storage is 55-85°F. (12.8-29.4°C.).

### 7.3 Specific end use(s)

- Refer to Section 1.2 - Relevant identified uses.

## Section 8 - Exposure Controls/Personal Protection

### 8.1 Control parameters

Exposure Limits/Guidelines				
	Result	Denmark	Germany DFG	Germany TRGS
1,1,1,2-Tetrafluoroethane (811-97-2)	TWAs	Not established	Not established	1000 ppm TWA AGW (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed, exposure factor 8); 4200 mg/m <sup>3</sup> TWA AGW (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed, exposure factor 8)

	Ceilings	Not established	8000 ppm Peak; 33600 mg/m <sup>3</sup> Peak	Not established
	MAKs	Not established	1000 ppm TWA MAK; 4200 mg/m <sup>3</sup> TWA MAK	Not established
Diethylene Glycol (111-46-6)	TWAs	2.5 ppm TWA; 11 mg/m <sup>3</sup> TWA	Not established	10 ppm TWA AGW (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed; sum of vapor and aerosol, exposure factor 4); 44 mg/m <sup>3</sup> TWA AGW (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed; sum of vapor and aerosol, exposure factor 4)
	Ceilings	Not established	40 ppm Peak (can occur as vapor and aerosol at the same time); 176 mg/m <sup>3</sup> Peak (can occur as vapor and aerosol at the same time)	Not established
	MAKs	Not established	10 ppm TWA MAK (can occur as vapor and aerosol at the same time); 44 mg/m <sup>3</sup> TWA MAK (can occur as vapor and aerosol at the same time)	Not established
Dipropylene Glycol (25265-71-8)	TWAs	Not established	Not established	100 mg/m <sup>3</sup> TWA AGW (The risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed; sum of vapor and aerosol, inhalable fraction, exposure factor 2)
	Ceilings	Not established	200 mg/m <sup>3</sup> Peak (can occur as vapor and aerosol at the same time, inhalable fraction)	Not established
	MAKs	Not established	100 mg/m <sup>3</sup> TWA MAK (can occur as vapor and aerosol at the same time, inhalable fraction)	Not established

## Exposure Control Notations

### Germany DFG

- Diethylene Glycol (111-46-6): **Pregnancy:** (no risk to embryo/fetus if exposure limits adhered to)
- Dipropylene Glycol (25265-71-8): **Pregnancy:** (no risk to embryo/fetus if exposure limits adhered to)
- 1,1,1,2-Tetrafluoroethane (811-97-2): **Pregnancy:** (no risk to embryo/fetus if exposure limits adhered to)

## 8.2 Exposure controls

### Engineering Measures/Controls

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Personal Protective Equipment

#### Respiratory

- In case of insufficient ventilation, wear suitable respiratory equipment.

#### Eye/Face

- Wear safety glasses.

#### Skin/Body

- Wear appropriate gloves.

### Environmental Exposure Controls

- Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways. Follow best practice for site management and disposal of waste.

### Key to abbreviations

MAK = Maximale Arbeitsplatz Konzentration is the maximum permissible concentration

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

TWAEV = Time-Weighted Average Exposure Value

## Section 9 - Physical and Chemical Properties

### 9.1 Information on Basic Physical and Chemical Properties

Material Description			
Physical Form	Aerosol	Appearance/Description	Red viscous liquid with mildly sweet odor.
Color	Red	Odor	Mildly sweet.
Odor Threshold	Data lacking		
General Properties			
Boiling Point	Data lacking	Melting Point/Freezing Point	Data lacking
Decomposition Temperature	Data lacking	pH	Data lacking
Specific Gravity/Relative Density	= 1.03 Water=1	Water Solubility	Partially Soluble
Viscosity	Data lacking	Explosive Properties	Data lacking
Oxidizing Properties:	Data lacking		
Volatility			
Vapor Pressure	> 200 psi	Vapor Density	Data lacking
Evaporation Rate	Data lacking	VOC (Wt.)	Data lacking
VOC (Vol.)	Data lacking		
Flammability			
Flash Point	Data lacking	UEL	Data lacking
LEL	Data lacking	Autoignition	Data lacking
Flammability (solid, gas)	Data lacking		
Environmental			
Octanol/Water Partition coefficient	Data lacking		

### 9.2 Other Information

- No additional physical and chemical parameters noted.

## Section 10: Stability and Reactivity

### 10.1 Reactivity

- No dangerous reaction known under conditions of normal use. Polymerizes with isocyanate-containing substances.

### 10.2 Chemical stability

- Stable under normal temperatures and pressures.

### 10.3 Possibility of hazardous reactions

- Hazardous polymerization not indicated.

### 10.4 Conditions to avoid

- Excess heat. Incompatible materials.

### 10.5 Incompatible materials

- Oxidizing agents.

### 10.6 Hazardous decomposition products

- Carbon monoxide, carbon dioxide, smoke, and irritant decomposition byproducts.

## Section 11 - Toxicological Information

### 11.1 Information on toxicological effects

Components		
Diethylene Glycol (< 15%)	111-46-6	<b>Acute Toxicity:</b> Skin-Rabbit LD50 • 11890 mg/kg; <b>Irritation:</b> Eye-Rabbit • 50 mg • Mild irritation; Skin-Rabbit • 500 mg • Mild irritation
Dipropylene Glycol (< 15%)	25265-71-8	<b>Acute Toxicity:</b> Ingestion/Oral-Rat LD50 • 14850 mg/kg; Skin-Rabbit LD50 • >20 mL/kg
1,1,1,2-Tetrafluoroethane (10% TO 15%)	811-97-2	<b>Acute Toxicity:</b> Inhalation-Rat LC50 • 1500 g/m <sup>3</sup> 4 Hour(s)

GHS Properties	Classification
<b>Acute toxicity</b>	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking WHMIS 2015 • Data lacking
<b>Skin corrosion/Irritation</b>	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking WHMIS 2015 • Data lacking
<b>Serious eye damage/Irritation</b>	EU/CLP • Data lacking OSHA HCS 2012 • Eye Mild Irritation 2B WHMIS 2015 • Eye Mild Irritation 2B
<b>Skin sensitization</b>	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking WHMIS 2015 • Data lacking
<b>Respiratory sensitization</b>	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking WHMIS 2015 • Data lacking
<b>Aspiration Hazard</b>	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking WHMIS 2015 • Data lacking
<b>Carcinogenicity</b>	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking WHMIS 2015 • Data lacking
<b>Germ Cell Mutagenicity</b>	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking WHMIS 2015 • Data lacking
<b>Toxicity for Reproduction</b>	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking WHMIS 2015 • Data lacking
<b>STOT-SE</b>	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking WHMIS 2015 • Data lacking
<b>STOT-RE</b>	EU/CLP • Specific Target Organ Toxicity Repeated Exposure 2 OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 2 WHMIS 2015 • Specific Target Organ Toxicity Repeated Exposure 2

### Potential Health Effects



**Inhalation****Acute (Immediate)**

- This material is a simple asphyxiant. May displace or reduce oxygen available for breathing especially in confined spaces. If this material is released in a small, poorly ventilated area (i.e. an enclosed or confined space), an oxygen-deficient environment may occur. Individuals breathing such an atmosphere may experience symptoms which include headaches, ringing in ears, dizziness, drowsiness, unconsciousness, nausea, vomiting, and depression of all the senses. Under some circumstances of over-exposure, death may occur. The following effects associated with decreased levels of oxygen: increase in breathing and pulse rate, emotional upset, abnormal fatigue, nausea, vomiting, collapse, loss of consciousness, convulsive movements, respiratory collapse and death.

**Chronic (Delayed)**

- No data available

**Skin****Acute (Immediate)**

- No data available

**Chronic (Delayed)**

- No data available

**Eye****Acute (Immediate)**

- Causes eye irritation.

**Chronic (Delayed)**

- No data available

**Ingestion****Acute (Immediate)**

- The product is nontoxic by ingestion, but ingestion may cause nausea, vomiting, and/or gastrointestinal irritation.

**Chronic (Delayed)**

- No data available

**Other****Chronic (Delayed)**

- May cause damage to kidneys and/or gastrointestinal system through prolonged or repeated exposure.

**Key to abbreviations**

LC = Lethal Concentration

LD = Lethal Dose

**Section 12 - Ecological Information****12.1 Toxicity**

- Material data lacking.

**12.2 Persistence and degradability**

- Material data lacking.

**12.3 Bioaccumulative potential**

- Material data lacking.

**12.4 Mobility in Soil**

- Material data lacking.

**12.5 Results of PBT and vPvB assessment**

- No PBT and vPvB assessment has been conducted.

**12.6 Other adverse effects**

- No studies have been found.

**Section 13 - Disposal Considerations**

### 13.1 Waste treatment methods

**Product waste**

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

**Packaging waste**

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN3500	CHEMICAL UNDER PRESSURE, N.O.S. (contains fluorinated hydrocarbon, nitrogen)	2.2	Not relevant	NDA
TDG	UN3500	CHEMICAL UNDER PRESSURE, N.O.S. (contains fluorinated hydrocarbon, nitrogen)	2.2	Not relevant	NDA
IMO/IMDG	UN3500	CHEMICAL UNDER PRESSURE, N.O.S. (contains fluorinated hydrocarbon, nitrogen)	2.2	Not relevant	NDA
ADN	UN3500	CHEMICAL UNDER PRESSURE, N.O.S. (contains fluorinated hydrocarbon, nitrogen)	2.2	Not relevant	NDA
ADR/RID	UN3500	CHEMICAL UNDER PRESSURE, N.O.S. (contains fluorinated hydrocarbon, nitrogen)	2.2	Not relevant	NDA
IATA/ICAO	UN3500	CHEMICAL UNDER PRESSURE, N.O.S. (contains fluorinated hydrocarbon, nitrogen)	2.2	Not relevant	NDA

**14.6 Special precautions for user**

- None specified.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

- Data lacking.

## Section 15 - Regulatory Information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**SARA Hazard Classifications** • Pressure(Sudden Release of), Acute, Chronic

State Right To Know				
Component	CAS	MA	NJ	PA
Diethylene Glycol	111-46-6	No	No	Yes
1,1,1,2-Tetrafluoroethane	811-97-2	No	No	No
Dipropylene Glycol	25265-71-8	No	No	Yes

Inventory						
Component	CAS	Canada DSL	Canada NDSL	EU EINECS	EU ELNICS	TSCA
Diethylene Glycol	111-46-6	Yes	No	Yes	No	Yes

1,1,1,2-Tetrafluoroethane	811-97-2	Yes	No	Yes	No	Yes
Dipropylene Glycol	25265-71-8	Yes	No	Yes	No	Yes

## Belgium

### Labor

#### Belgium - Substances and Preparations - Carcinogens and Mutagens

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

## Bulgaria

### Environment

#### Bulgaria - Air Quality - Maximum Admissible Hazardous Contaminant Levels - 24 Hour

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

#### Bulgaria - Air Quality - Maximum Admissible Hazardous Contaminant Levels - 30 Minute

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

#### Bulgaria - Air Quality - Maximum Admissible Hazardous Contaminant Levels - Annual

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

## Canada

### Labor

#### Canada - WHMIS 1988 - Classifications of Substances

• Diethylene Glycol	111-46-6	D1B
• 1,1,1,2-Tetrafluoroethane	811-97-2	A
• Dipropylene Glycol	25265-71-8	Not Listed

#### Canada - WHMIS 1988 - Ingredient Disclosure List

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

### Environment

#### Canada - CEPA - Priority Substances List

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

## Denmark

### Environment

#### Denmark - List of Undesirable Substances - Product Groups/Function

• Diethylene Glycol	111-46-6	Not Listed
		Spray canisters (listed under Fluorinated greenhouse gases); Refrigeration systems

• 1,1,1,2-Tetrafluoroethane	811-97-2	(listed under Fluorinated greenhouse gases); Insulating foam (listed under Fluorinated greenhouse gases)
• Dipropylene Glycol	25265-71-8	Not Listed

## Europe

### Other

#### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification (OBSOLETE)

• Diethylene Glycol	111-46-6	Xn; R22
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

#### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits (OBSOLETE)

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

#### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling (OBSOLETE)

• Diethylene Glycol	111-46-6	Xn R:22 S:(2)-46
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

#### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations (OBSOLETE)

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

#### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases (OBSOLETE)

• Diethylene Glycol	111-46-6	S:(2)-46
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

## Germany

### Labor

#### Germany - Immission Control - Qualifying Quantities for Major Accident Prevention

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

#### Germany - Immission Control - Qualifying Quantities for Safety Reporting

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

#### Germany - TRGS 505 - Specific Lead Regulations

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

### Environment

#### Germany - TA Luft - Types and Classes

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed

• Dipropylene Glycol	25265-71-8	Not Listed
<b>Germany - TA Luft - Emission Limits for Carcinogenic Substances</b>		
• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed
<b>Germany - TA Luft - Emission Limits for Fibers</b>		
• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed
<b>Germany - TA Luft - Emission Limits for Inorganic Dusts</b>		
• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed
<b>Germany - TA Luft - Emission Limits for Inorganic Gases</b>		
• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed
<b>Germany - TA Luft - Emission Limits for Organic Substances</b>		
• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed
<b>Germany - Water Classification (VwVwS) - Annex 1</b>		
• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed
<b>Germany - Water Classification (VwVwS) - Annex 2 - Water Hazard Classes</b>		
• Diethylene Glycol	111-46-6	ID Number 79, hazard class 1 - low hazard to waters
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed
<b>Germany - Water Classification (VwVwS) - Annex 3</b>		
• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	ID Number 2350, hazard class 1 - low hazard to waters
• Dipropylene Glycol	25265-71-8	ID Number 3419, hazard class 1 - low hazard to waters

## United States

### Labor

#### U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

#### U.S. - OSHA - Specifically Regulated Chemicals

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

**Environment****U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants**

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

**U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities**

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

**U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities**

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

**U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs**

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

**U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs**

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

**U.S. - CERCLA/SARA - Section 313 - Emission Reporting**

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

**U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing**

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

**United States - California****Environment****U.S. - California - Proposition 65 - Carcinogens List**

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

**U.S. - California - Proposition 65 - Developmental Toxicity**

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

**U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)**

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

**U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)**

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

**U.S. - California - Proposition 65 - Reproductive Toxicity - Female**

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

**U.S. - California - Proposition 65 - Reproductive Toxicity - Male**

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

**United States - Pennsylvania****Labor****U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List**

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

**U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances**

• Diethylene Glycol	111-46-6	Not Listed
• 1,1,1,2-Tetrafluoroethane	811-97-2	Not Listed
• Dipropylene Glycol	25265-71-8	Not Listed

**15.2 Chemical Safety Assessment**

- No Chemical Safety Assessment has been carried out.

**Section 16 - Other Information****Relevant Phrases (code & full text)**

- H302 - Harmful if swallowed

**Revision Date**

- 27/February/2018

**Preparation Date**

- 08/January/2018

**Disclaimer/Statement of Liability**

- The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company, LLC assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.

**Key to abbreviations**

NDA = No Data Available