



Rust-Go® Primer VOC

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Rust-Go Primer VOC

Product Code: 1523

Intended Use of the Product

Quick-drying, rust inhibitive primer. For professional use only.

Name, Address, and Telephone of the Responsible Party

Manufacturer

The Garland Company, Inc.
3800 East 91st Street
Cleveland, Ohio 44105-2197
T-800-762-8225
F-216-641-0633
www.garlandco.com

Supplier

The Garland Company, Inc.
3800 East 91st Street
Cleveland, Ohio 44105-2197
T-800-762-8225
F-216-641-0633
www.garlandco.com

Garland Canada, Inc.
209 Carrier Drive
Toronto, Ontario M9W 5Y8
T-416-747-7995
F-416-747-1980
www.garlandco.com

Emergency Telephone Number

Emergency Number: 1-800-262-8200 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

| | |
|--------------------------|------|
| Flam. Gas 1 | H220 |
| Flam. Liq. 1 | H224 |
| Carc. 2 | H225 |
| Flam. Liq. 4 | H227 |
| Press. Gas Liquefied gas | H280 |
| Acute Tox. 4 | H302 |
| Asp.Tox. 1 | H304 |
| Acute Tox. 1 | H315 |
| Skin Irrit. 2 | H317 |
| Eye Dam. 1 | H318 |
| Flam. Liq. 2 | H319 |
| Eye Irr. 2B | H320 |
| Skin Sens. 1 | H330 |
| Eye Irrit. 2A | H331 |
| Carc. 2 | H332 |
| Carc. 1B | H335 |
| STOT SE 3 | H350 |
| STOT SE 3 | H351 |
| STOT RE 1 | H372 |
| STOT RE 2 | H373 |
| Aquatic Acute 2 | H401 |
| Aquatic Acute 3 | H402 |
| Aquatic Chronic 3 | H412 |

Label Elements

GHS-US Labeling

Rust-Go® Primer VOC

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

Hazard Pictograms (GHS-US)

:



GHS02



GHS07



GHS08



GHS09

Signal Word (GHS-US)

:

Danger

Hazard Statements (GHS-US)

:

H220-Extremely flammable gas
H224-Extremely flammable liquid and vapor
H225-Highly flammable liquid and vapor
H227-Combustible liquid
H280-Contains gas under pressure; may explode if heated
H302-Harmful if swallowed
H304-May be fatal if swallowed and enters airways
H315-Causes skin irritation
H317-May cause an allergic skin reaction
H318-Causes serious eye damage
H319-Causes serious eye irritation
H320-Causes eye irritation
H330-Fatal if inhaled
H331-Toxic if inhaled
H332-Harmful if inhaled
H335-May cause respiratory irritation
H340-May cause genetic defects by route of exposure if conclusively proven that no other route applies
H350-May cause cancer by route of exposure if conclusively proven that no other route applies
H351-Suspected of causing cancer by route of exposure if conclusively proven that no other route applies.
H372-Causes damage to organs through prolonged or repeated exposure by route of exposure if conclusively proven that no other route applies
H373-May cause damage to organs through prolonged or repeated exposure by route of exposure if conclusively proven that no other route
H401-Toxic to aquatic life
H402-harmful to aquatic life
H412-harmful to aquatic life with long lasting effects

Precautionary Statements (GHS-US)

:

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting/ equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe gas.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash face, hands and any exposed skin thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P281 - Use personal protective equipment as required.
P280 - Wear protective gloves/protective clothing/eye protection/face

Rust-Go® Primer VOC

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

protection.

P284 - Wear respiratory protection.

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P301 + P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 - IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 - IF exposed or concerned: Get medical advice/attention.

P310 - Immediately call a POISON CENTER or doctor/physician.

P311 - Call a POISON CENTER or doctor/physician.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P314 - Get medical advice/attention if you feel unwell.

P320 - Specific treatment is urgent (see supplemental first aid instructions on this label).

P321 - Specific treatment (see supplemental first aid instructions on this label).

P330 - Rinse mouth.

P331 - Do NOT induce vomiting.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

P362 - Take off contaminated clothing and wash before reuse.

P363 - Wash contaminated clothing before reuse.

P370 + P378 - In case of fire: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P381 - Eliminate all ignition sources if safe to do so.

P403 - Store in a well-ventilated place.

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P410 + P403 - Protect from sunlight. Store in a well-ventilated place.

P501 - Dispose of contents/container to an approved landfill.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component

| Name | Product Identifier | % (w/w) | Classification (GHS-US) |
|-----------------|--------------------|---------|---|
| Benzyl chloride | (CAS No) 100-44-7 | | Flam. Liq. 4, H227 Acute Tox. 4, H302 Acute Tox. 1, H315 Skin Irrit. 2, H317 Eye Dam. 1, H318 Skin Sens. 1, H330 Carc. 1B, H335 STOT SE 3, H350 STOT RE 2, H373 |
| 1,4-Dioxane | (CAS No) 123-91-1 | | Flam. Liq. 2, H319 Eye Irrit. 2A, H335 Carc. 2, H225 |

Rust-Go® Primer VOC

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

| | | | |
|-------------------|---------------------|-------|---|
| | | | STOT SE 3, H351 |
| Calcium Carbonate | (CAS No) 1317-65-3 | 5-10 | Acute Tox. Oral 4, H302 Skin Corr. Irr. 2, H315 Eye Irr. 2B, H320 STOT RE 1, H372 |
| Titanium dioxide | (CAS No) 13463-67-7 | 10-30 | Carc. 2, H351 |
| Acetaldehyde | (CAS No) 75-07-0 | | Flam. Liq. 1, H224 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Acute 3, H402 |
| Ethylene oxide | (CAS No) 75-21-8 | | Flam. Gas 1, H220 Press. Gas Liquefied gas, H280 Acute Tox. 3, H315 Skin Irrit. 2, H319 Eye Irrit. 2A, H331 Muta.1B, H335 Carc. 1B, H340 STOT SE 3, H350 Aquatic Chronic 3, H412 |
| Water | (CAS No) 7731-18-5 | 30-60 | |
| Acrylic Copolymer | Trade Secret | 10-30 | |
| Ethyl benzene | (CAS No) 100-41-4 | | Flam. Liq. 2, H225 Acute Tox. 4, H351 Carc. 2, H332 STOT RE 2, H373 Asp.Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412 |

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: May cause irritation of respiratory tract.

Skin Contact: Substance may cause slight skin irritation.

Eye Contact: May cause slight irritation.

Ingestion: Ingestion can cause irritation to mucous membranes.

Most Important Symptoms and Effects Both Acute and Delayed

General: No further relevant information available.

Indication of Immediate Medical Attention and Special Treatment Needed

General: No further relevant information available.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media: Not available.

Special Hazards Arising From the Substance or Mixture

Hazardous Combustion Products: Not available.

Fire and Explosion Hazards: None.

Advice for Firefighters

Fire Fighting Procedures: Exercise caution when fighting any chemical fire.

Rust-Go® Primer VOC

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

Protection During Firefighting: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use personal protective equipment.

Environmental Precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Keep out of waterways.

Methods and Materials for Containment and Cleaning Up

For Containment and Cleaning Up: Dike with inert absorbent material. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. Clean contaminated surface thoroughly. After cleaning, flush away traces with water.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

General Handling: Handle in accordance with good industrial hygiene and safety practice. Wear personal protective equipment.

Avoid contact with skin and eyes.

Conditions for Safe Storage

General: Keep container tightly closed in a dry and well-ventilated place. Keep at temperatures above 0°C.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

| Chemical Name | ACGIH TLV | OSHA PEL | Ontario TWAEV | Mexico |
|-------------------|-------------------------------|---|--|--|
| Benzyl chloride | TWA: 1 ppm | TWA: 1 ppm TWA: 5 mg/m ³ | TWA: 1 ppm TWA: 5 mg/m ³ | TWA: 1 ppm TWA: 5 mg/m ³ |
| 1,4-Dioxane | TWA: 20 ppm Skin | TWA: 100 ppm TWA: 360 mg/m ³ Skin | TWA: 20 ppm Skin | STEL: 100 ppm STEL: 360 mg/m ³ TWA: 90 mg/m ³ TWA: 25 ppm |
| Calcium Carbonate | | TWA: 15 mg/m ³ TWA: 5 mg/m ³ | TWA: 10 mg/m ³ | STEL: 20 mg/m ³ TWA: 10 mg/m ³ |
| Titanium dioxide | TWA: 10 mg/m ³ | TWA: 15 mg/m ³ | TWA: 10 mg/m ³ | STEL: 20 mg/m ³ TWA: 10 mg/m ³ |
| Acetaldehyde | Ceiling: 25 ppm | TWA: 360 mg/m ³ TWA: 200 ppm | CEV: 25 ppm | Ceiling: 45 mg/m ³ Ceiling: 25 ppm |
| Ethylene oxide | TWA: 1 ppm | TWA: 1 ppm | STEL: 18 mg/m ³ STEL: 10 ppm TWA: 1.8 mg/m ³ TWA: 1 ppm | TWA: 1 ppm TWA: 2 mg/m ³ |
| Ethyl benzene | TWA: 100 ppm STEL: 125 ppm | TWA: 100 ppm TWA: 435 mg/m ³ | STEL: 540 mg/m ³ STEL: 125 ppm TWA: 100 ppm TWA: 435 mg/m ³ | STEL: 125 ppm STEL: 545 mg/m ³ TWA: 100 ppm TWA: 435 mg/m ³ |

| Chemical Name | NIOSH IDLH |
|------------------|------------------------|
| Benzyl chloride | 10 ppm |
| 1,4-Dioxane | 500 ppm |
| Titanium dioxide | 5000 mg/m ³ |
| Acetaldehyde | 2000 ppm |
| Ethylene oxide | 800 ppm |
| Ethyl benzene | 800 ppm |

Control Parameters

Appropriate Engineering Controls: Do not allow ventilation equipment to draw material odors indoors.

Personal Protective Equipment

Rust-Go® Primer VOC

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

- Eye/face Protection :** Tightly fitting safety goggles.
- Skin Protection:** Long sleeved clothing. Protective gloves.
- Respiratory Protection :** No special protective equipment required. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
- Hand Protection:** Wear impervious gloves such as vinyl to minimize contact with skin.



Environmental Exposure Controls: No specific controls are needed.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

| | |
|---|--|
| Physical State | : Liquid |
| Color | : White |
| Odor | : Slight |
| Odor Threshold | : Not applicable |
| pH | : 9.5 |
| Melting Point | : No test data available |
| Freezing Point | : 32°F / 0°C |
| Boiling Point (760 mm Hg) | : 212-212°F / 100100°C |
| Density | : 10.64 (lbs/gal) |
| Flash Point – Closed Cup | : 201°F / 94°C |
| Evaporation Rate (Butyl Acetate = 1) | : 0.010 (ether = 1) |
| Flammability (solid, gas) | : Not applicable |
| Flammability Limits in Air | : Lower: No test data available; Upper: No test data available |
| Vapor Pressure | : Not determined. |
| Vapor Density (Air = 1) | : Lighter than air |
| Specific Gravity (H ₂ O = 1) | : 1.2748 |
| Solubility in Water (by wt) | : Partial |
| Explosion Limits | : Not available |
| Volatiles | : Not available |
| VOC | : <50 g/L |

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Not available.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization does not occur under normal conditions.

Conditions to Avoid: Temperatures above 0°C.

Incompatible Materials: No materials to be especially mentioned.

Hazardous Decomposition Products: None under normal use.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Component Information

| Chemical Name | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|------------------|-----------------|-------------------|---------------------|
| Benzyl chloride | 340 mg/kg Rat | | 0.74 mg/L Rat 4 h |
| 1,4-Dioxane | 7120 mg/kg Rat | 7600 µL/kg Rabbit | |
| Titanium dioxide | 10000 mg/kg Rat | | |
| Acetaldehyde | 661 mg/kg Rat | 3540 mg/kg Rabbit | 13300 mg/kg Rat 4 h |

Rust-Go® Primer VOC

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

| | | | |
|----------------|----------------|--------------------|--|
| Ethylene oxide | 0.05 mg/kg Rat | | 1.44 mg/L Rat 4 h 800 ppm Rat 4 h 9 mg/L Rat 1 h |
| Ethyl benzene | 3500 mg/kg Rat | 15354 mg/kg Rabbit | 17.2 mg/L Rat 4 h |

Chronic Toxicity

California Proposition 65: WARNING: This product contains a chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

| Chemical Name | ACGIH | IARC | NTP | OSHA | Mexico |
|------------------|-------|----------|------------------------|------|--------|
| Benzyl chloride | A3 | Group 2A | | X | A3 |
| 1,4-Dioxane | A3 | Group 2B | Reasonably Anticipated | X | |
| Titanium dioxide | | Group 2B | | X | |
| Acetaldehyde | A3 | Group 2B | Reasonably Anticipated | X | A3 |
| Ethylene oxide | A2 | Group 1 | Known | X | A2 |
| Ethyl benzene | A3 | Group 2B | | X | |

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Ecotoxicity effects

Benzyl chloride

Microtox Data

Photobacterium phosphoreum EC50=1.92 mg/L (5 min)

Photobacterium phosphoreum EC50=2.25 mg/L (15 min)

Photobacterium phosphoreum EC50=2.97 mg/L (30 min)

Water Flea Data

Daphnia magna EC50=1.3 mg/L (24 h)

1,4-Dioxane

Microtox Data

Photobacterium phosphoreum EC50=610 mg/L (5 min)

Photobacterium phosphoreum EC50=668 mg/L (15 min)

Photobacterium phosphoreum EC50=733 mg/L (30 min)

Water Flea Data

water flea EC50=163 mg/L (48 h)

Acetaldehyde

Freshwater Algae Data

Nitzschia linearis EC50=237 - 249 mg/L (120 h)

Microtox Data

Photobacterium phosphoreum EC50=280.6 mg/L (15 min)

Photobacterium phosphoreum EC50=280.6 mg/L (25 min)

Photobacterium phosphoreum EC50=280.6 mg/L (5 min)

Water Flea Data

Daphnia magna EC50=48.3 mg/L (48 h)

water flea EC50=9000 mg/L (48 h)

Ethylene oxide

Water Flea Data

Daphnia magna EC50=137 mg/L (48 h)

Rust-Go® Primer VOC

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

Benzyl chloride

Ethyl benzene

Freshwater Algae Data

Selenastrum capricornutum EC50=4.6 mg/L (72 h)

Selenastrum capricornutum EC50>438 mg/L (96 h)

Microtox Data

Photobacterium phosphoreum EC50=9.68 mg/L (30 min)

Nitrosomonas EC50=96 mg/L (24 h)

Water Flea Data

Daphnia magna EC501.8 - 2.4 mg/L (48 h)

Persistence/Degradability:

Not available

Bioaccumulation/ Accumulation:

Not available

Mobility in Environmental Media:

Not available

Benzyl chloride

log Pow = 2.3

1,4-Dioxane

log Pow = -0.42

Acetaldehyde

log Pow = 0.5

Ethylene oxide

log Pow = -0.3

Ethyl benzene

log Pow = 3.118

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of in accordance with local, state, and federal regulations.

Unused and Contaminated Product: Empty containers should be taken for local recycling, recovery or waste disposal.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : Not regulated
Hazard Class :
Identification Number :
Packing Group :

14.2 In Accordance with IMDG

Proper Shipping Name : Not regulated
Hazard Class :
Identification Number :
Packing Group :

14.3 In Accordance with IATA

Proper Shipping Name

Rust-Go® Primer VOC

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A

Date of issue: 10/12/2015

Hazard Class : Not regulated
Identification Number :
Packing Group :

14.4 In Accordance with Mexico

Proper Shipping Name : Not regulated
Hazard Class :
Identification Number :
Packing Group :

SECTION 15: REGULATORY INFORMATION

International Inventories

All of the components in the product are on the following Inventory lists:

| Chemical Name | TSCA | DSL | NDSL | EINECS | ELINCS | ENCS | CHINA | KECL | PICCS | AICS |
|-------------------|------|-----|------|--------|--------|------|-------|------|-------|------|
| Benzyl chloride | X | X | X | X | X | X | X | X | X | X |
| 1,4-Dioxane | X | X | X | X | X | X | X | X | X | X |
| Calcium Carbonate | X | X | X | X | X | X | X | X | X | X |
| Titanium dioxide | X | X | X | X | X | X | X | X | X | X |
| Acetaldehyde | X | X | X | X | X | X | X | X | X | X |
| Ethylene oxide | X | X | X | X | X | X | X | X | X | X |
| Water | X | X | X | X | X | X | X | X | X | X |
| Acrylic Copolymer | X | X | X | X | X | X | X | X | X | X |
| Ethyl benzene | X | X | X | X | X | X | X | X | X | X |

TSCA Complies
DSL Complies
NDSL Complies
EINECS Complies
ELINCS Complies
ENCS Complies
CHINA Complies
KECL Complies
PICCS Complies
AICS Complies

USA

Federal Regulations:

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40n of the Code of Federal Regulations, Part 372.

| Chemical Name | SARA 313 - Threshold Values |
|-----------------------------------|-----------------------------|
| Benzyl chloride (CAS #: 100-44-7) | 1.0% |
| 1,4-Dioxane (CAS #: 123-91-1) | 0.1% |
| Acetaldehyde (CAS #: 75-07-0) | 0.1% |
| Ethylene oxide (CAS #: 75-21-8) | 0.1% |
| Ethyl benzene (CAS #: 100-41-4) | < 5% |

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

Rust-Go® Primer VOC

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: N/A Date of issue: 10/12/2015

This product contains no HAPs.

State Regulations:

California Proposition 65

WARNING: This product contains a chemical(s) known to the State of California to cause cancer.

State Right-to-Know

| Chemical Name | CAS-No | Category | Type |
|------------------|------------|------------|---------------------|
| Benzyl chloride | 100-44-7 | Carcinogen | |
| 1,4-Dioxane | 123-91-1 | Carcinogen | |
| Acetaldehyde | 75-07-0 | Carcinogen | |
| Ethylene oxide | 75-21-8 | Carcinogen | Female Reproductive |
| Ethyl benzene | 100-41-4 | Carcinogen | |
| Titanium Dioxide | 13463-67-7 | Carcinogen | |

State Right-to-Know

| Chemical Name | Massachusetts | New Jersey | Pennsylvania | Illinois | Rhode Island |
|-------------------|---------------|------------|--------------|----------|--------------|
| Benzyl chloride | X | X | X | X | X |
| 1,4-Dioxane | X | X | X | X | X |
| Calcium Carbonate | X | | X | | X |
| Titanium dioxide | X | X | X | | X |
| Acetaldehyde | X | X | X | X | X |
| Ethylene oxide | X | X | X | X | X |
| Ethyl benzene | X | X | X | X | X |

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

Rust-Go® Primer VOC

WHMIS Classification Not determined

SECTION 16: OTHER INFORMATION

- Revision Date** : October 12, 2015
- Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.
- Party Responsible for the Preparation of This Document** : The Garland Company, Inc.
3800 East 91st Street
Cleveland, Ohio 44105-2197
T-1800-762-8225
F-216-641-0633

This information is based on our knowledge as of the Revision Date and is intended to describe the product only for the purposes of health, safety and environmental requirements as of the Revision Date. It should not therefore be construed as guaranteeing any specific property of the product nor as providing any warranty, expressed or implied. The user assumes all responsibility, liability, risk of loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use, or disposal of the product.