

# SAFETY DATA SHEET

## 1. Identification

**Material name:** TP6100 BM (AKA PQ-6100(BM)MEMBRANE C)  
**Material:** 87210BM860

**Recommended use and restriction on use**

**Recommended use:** Adhesive  
**Restrictions on use:** Not known.

**Manufacturer/Importer/Supplier/Distributor Information**

Tremco U.S Sealants  
3735 Green Road  
Cleveland OH 44122  
US

<b>Contact person:</b>	EH&S Department
<b>Telephone:</b>	216-292-5000
<b>Emergency telephone number:</b>	1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

**Hazard Classification**

**Health Hazards**

Acute toxicity (Inhalation - dust and mist)	Category 4
Carcinogenicity	Category 1A

**Unknown toxicity - Health**

Acute toxicity, oral	0.096 %
Acute toxicity, dermal	18.27 %
Acute toxicity, inhalation, vapor	99.94 %
Acute toxicity, inhalation, dust or mist	80.79 %

**Unknown toxicity - Environment**

Acute hazards to the aquatic environment	80.07 %
Chronic hazards to the aquatic environment	100 %

**Label Elements**

**Hazard Symbol:**



**Signal Word:** Danger

**Hazard Statement:** Harmful if inhaled.  
May cause cancer.

**Precautionary Statement:  
Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Other hazards which do not result in GHS classification:**

None.

### 3. Composition/information on ingredients

**Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
Asphalt	8052-42-4	40 - 70%
Calcium carbonate	471-34-1	15 - 40%
Magnesite	546-93-0	15 - 40%
Paraffin Oil	64742-65-0	7 - 13%
Carbon Black	1333-86-4	1 - 5%
Paraffinic distillate	64742-04-7	1 - 5%
Amorphous silica	7631-86-9	0.1 - 1%
Zinc oxide	1314-13-2	0.1 - 1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

**Ingestion:**

Call a POISON CENTER/doctor/...if you feel unwell. Rinse mouth.

**Inhalation:**

Move to fresh air.

**Skin Contact:**

Wash skin thoroughly with soap and water. Get medical attention if symptoms occur.

**Eye contact:**

Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

**Most important symptoms/effects, acute and delayed**

**Symptoms:**

May cause skin and eye irritation.

**Indication of immediate medical attention and special treatment needed**

**Treatment:** Symptoms may be delayed.

## 5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

### Suitable (and unsuitable) extinguishing media

**Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical:** During fire, gases hazardous to health may be formed.

### Special protective equipment and precautions for firefighters

**Special fire fighting procedures:** No data available.

**Special protective equipment for fire-fighters:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** No data available.

**Methods and material for containment and cleaning up:** Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

**Notification Procedures:** In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

## 7. Handling and storage

**Precautions for safe handling:** Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.

**Conditions for safe storage, including any incompatibilities:** Store locked up.

## 8. Exposure controls/personal protection

### Control Parameters

#### Occupational Exposure Limits

Chemical Identity	type	Exposure Limit Values	Source
Asphalt - Inhalable fraction. - as benzene solubles	TWA	0.5 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (2011)
Calcium carbonate - Total dust.	PEL	15 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Magnesite - Total dust.	PEL	15 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Magnesite - Respirable fraction.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Paraffin Oil - Inhalable fraction.	TWA	5 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2014)
Paraffin Oil	PEL	500 ppm 2,000 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Paraffin Oil - Mist.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Paraffinic distillate - Mist.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Amorphous silica	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.8 mg/m <sup>3</sup>	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Zinc oxide - Respirable fraction.	TWA	2 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (2011)
	STEL	10 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (2011)
Zinc oxide - Fume.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Zinc oxide - Total dust.	PEL	15 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Zinc oxide - Respirable fraction.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	type	Exposure Limit Values	Source
Asphalt - Aerosol, inhalable. - as benzene solubles	TWA	0.5 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Asphalt - Inhalable fraction. - as benzene solubles	TWAEV	0.5 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Asphalt - Fume.	TWA	5 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium carbonate - Total dust.	STEL	20 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Magnesite - Total dust.	TWAEV	10 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Magnesite - Total dust.	TWA	10 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Paraffin Oil - Mist.	TWA	0.2 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	1 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Paraffin Oil - Mist.	TWAEV	5 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical

			Agents) (11 2010)
Paraffin Oil - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black	TWAEV	3.5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Paraffinic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Paraffinic distillate - Mist.	TWAEV	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Paraffinic distillate - Mist.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

**Appropriate Engineering Controls**

Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

**Individual protection measures, such as personal protective equipment**

**General information:**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory and eye protection may be needed in special circumstances, such as poorly ventilated spaces, heating, evaporation of liquids from large surfaces, spraying of mists, mechanical generation of dusts, drying of solids, etc.

**Eye/face protection:**

Wear safety glasses with side shields (or goggles).

**Skin Protection****Hand Protection:** Use suitable protective gloves if risk of skin contact.**Other:** Wear suitable protective clothing.**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product.**9. Physical and chemical properties****Appearance****Physical state:** solid**Form:** solid**Color:** Black**Odor:** Aromatic**Odor threshold:** No data available.**pH:** No data available.**Melting point/freezing point:** No data available.**Initial boiling point and boiling range:** No data available.**Flash Point:** No data available.**Evaporation rate:** Slower than Ether**Flammability (solid, gas):** No**Upper/lower limit on flammability or explosive limits****Flammability limit - upper (%):** No data available.**Flammability limit - lower (%):** No data available.**Explosive limit - upper (%):** No data available.**Explosive limit - lower (%):** No data available.**Vapor pressure:** No data available.**Vapor density:** Vapors are heavier than air and may travel along the floor and in the bottom of containers.**Relative density:** 1.33**Solubility(ies)****Solubility in water:** Insoluble in water**Solubility (other):** No data available.**Partition coefficient (n-octanol/water):** No data available.**Auto-ignition temperature:** No data available.**Decomposition temperature:** No data available.**Viscosity:** No data available.**10. Stability and reactivity****Reactivity:** No data available.**Chemical Stability:** Material is stable under normal conditions.

---

<b>Possibility of Hazardous Reactions:</b>	No data available.
<b>Conditions to Avoid:</b>	Avoid heat or contamination.
<b>Incompatible Materials:</b>	Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates).
<b>Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

**11. Toxicological information****Information on likely routes of exposure**

<b>Ingestion:</b>	May be ingested by accident. Ingestion may cause irritation and malaise.
<b>Inhalation:</b>	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
<b>Skin Contact:</b>	May be harmful in contact with skin.
<b>Eye contact:</b>	Eye contact is possible and should be avoided.

**Information on toxicological effects****Acute toxicity (list all possible routes of exposure)**

<b>Oral</b>	
<b>Product:</b>	ATEmix: 12,548.39 mg/kg
<b>Dermal</b>	
<b>Product:</b>	ATEmix: 2,527.38 mg/kg
<b>Inhalation</b>	
<b>Product:</b>	ATEmix: 3 mg/l

<b>Repeated dose toxicity</b>	
<b>Product:</b>	No data available.

<b>Skin Corrosion/Irritation</b>	
<b>Product:</b>	No data available.

<b>Serious Eye Damage/Eye Irritation</b>	
<b>Product:</b>	No data available.



**Specified substance(s):**

Asphalt	in vivo (Rabbit, 24 hrs): Not irritating
Calcium carbonate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Magnesite	In vitro (Reconstituted Corneal Epithelium model, 10 min): Not irritating
Paraffin Oil	in vivo (Rabbit, 24 hrs): Not irritating
Carbon Black	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Paraffinic distillate	in vivo (Rabbit, 24 - 72 hrs): Not irritating
Amorphous silica	in vivo (Rabbit, 24 hrs): Not irritating
Zinc oxide	in vivo (Rabbit, 24 - 72 hrs): Not irritating

**Respiratory or Skin Sensitization**

**Product:** No data available.

**Carcinogenicity**

**Product:** No data available.

**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Asphalt	Overall evaluation: Possibly carcinogenic to humans.
Paraffin Oil	Overall evaluation: Carcinogenic to humans. Overall evaluation: Not classifiable as to carcinogenicity to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
Paraffinic distillate	Overall evaluation: Carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:**

Paraffin Oil	Known To Be Human Carcinogen.
Paraffinic distillate	Known To Be Human Carcinogen.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

No carcinogenic components identified

**Germ Cell Mutagenicity**

**In vitro**  
**Product:** No data available.

**In vivo**  
**Product:** No data available.

**Reproductive toxicity**

**Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure**

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure**

**Product:** No data available.

**Aspiration Hazard**

**Product:** No data available.

**Other effects:** No data available.

<b>12. Ecological information</b>
-----------------------------------

**Ecotoxicity:**

**Acute hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Specified substance(s):**

Calcium carbonate LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): > 56,000 mg/l Mortality

Zinc oxide LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 2,246 mg/l Mortality

**Aquatic Invertebrates**

**Product:** No data available.

**Specified substance(s):**

Zinc oxide LC 50 (Water flea (*Daphnia magna*), 48 h): 24.6 mg/l Mortality

**Chronic hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Specified substance(s):**

Asphalt NOAEL (*Oncorhynchus mykiss*, 28 d):  $\geq$  1,000 mg/l interpreted

Paraffin Oil NOAEL (*Oncorhynchus mykiss*, 14 d):  $\geq$  1,000 mg/l QSAR

Carbon Black NOAEL (*Salmo sp.*, 30 d): 17 mg/l QSAR

Paraffinic distillate NOAEL (*Oncorhynchus mykiss*, 28 d): 20.01 mg/l QSAR

Zinc oxide NOAEL (*Oncorhynchus mykiss*, 30 d): 974  $\mu$ g/l interpreted

**Aquatic Invertebrates**

**Product:** No data available.

**Toxicity to Aquatic Plants**

**Product:** No data available.

## Persistence and Degradability

**Biodegradation**  
Product: No data available.

**BOD/COD Ratio**  
Product: No data available.

**Bioaccumulative Potential**  
**Bioconcentration Factor (BCF)**  
Product: No data available.

**Partition Coefficient n-octanol / water (log Kow)**  
Product: No data available.

**Mobility in Soil:** No data available.

**Other Adverse Effects:** No data available.

## 13. Disposal considerations

**Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Contaminated Packaging:** No data available.

## 14. Transport information

### TDG:

Not Regulated

### CFR / DOT:

Not Regulated

### IMDG:

Not Regulated

## 15. Regulatory information

### US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

None present or none present in regulated quantities.

**CERCLA Hazardous Substance List (40 CFR 302.4):**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Asphalt	100 lbs.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)****Hazard categories**

Immediate (Acute) Health Hazards

Delayed (Chronic) Health Hazard

**SARA 302 Extremely Hazardous Substance**

None present or none present in regulated quantities.

**SARA 304 Emergency Release Notification**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Asphalt	100 lbs.
Zinc oxide	

**SARA 311/312 Hazardous Chemical**

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Asphalt	500 lbs
Calcium carbonate	500 lbs
Magnesite	500 lbs
Paraffin Oil	500 lbs
Carbon Black	500 lbs
Paraffinic distillate	500 lbs
Amorphous silica	500 lbs
Zinc oxide	500 lbs

**SARA 313 (TRI Reporting)**

None present or none present in regulated quantities.

**Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)**

None present or none present in regulated quantities.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):**

None present or none present in regulated quantities.

**US State Regulations****US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

## US. New Jersey Worker and Community Right-to-Know Act

### Chemical Identity

Asphalt  
Calcium carbonate  
Magnesite  
Paraffin Oil  
Carbon Black  
Paraffinic distillate

## US. Massachusetts RTK - Substance List

### Chemical Identity

Asphalt  
Calcium carbonate  
Magnesite  
Paraffin Oil  
Carbon Black  
Paraffinic distillate  
Crystalline Silica (Quartz)/ Silica Sand

## US. Pennsylvania RTK - Hazardous Substances

### Chemical Identity

Asphalt  
Calcium carbonate  
Paraffin Oil  
Carbon Black  
Paraffinic distillate

## US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

### Other Regulations:

<b>Regulatory VOC (less water and exempt solvent):</b>	0 g/l
<b>VOC Method 310:</b>	0.00 %

### Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are

	not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

**16. Other information, including date of preparation or last revision**

<b>Revision Date:</b>	07/30/2015
<b>Version #:</b>	1.0
<b>Further Information:</b>	No data available.
<b>Disclaimer:</b>	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.