



Weatherking® Flashing Adhesive

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: 05/13/2015

Date of issue: 06/01/2015

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mastic

Product Name: Weatherking® Flashing Adhesive

Product Code: 7338

Intended Use of the Product

Cold process, modified flashing adhesive. For professional use only.

Name, Address, and Telephone of the Responsible Party

Manufacturer

The Garland Company, Inc.
3800 East 91st Street
Cleveland, Ohio 44105-2197
T-800-762-8225
F-216-641-0633
www.garlandco.com

Supplier

The Garland Company, Inc.
3800 East 91st Street
Cleveland, Ohio 44105-2197
T-800-762-8225
F-216-641-0633
www.garlandco.com

Garland Canada, Inc.
209 Carrier Drive
Toronto, Ontario M9W 5Y8
T-416-747-7995
F-416-747-1980
www.garlandco.com

Emergency Telephone Number

Emergency Number: 1-800-262-8200 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Asp. Tox. 1	H304
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Flam. Liq. 2	H225
Flam. Liq. 3	H226
Acute Tox. 4 (Inhalation:vapor)	H332
STOT SE 3	H335
Muta. 1B	H340
Carc. 1B	H350
Carc. 2	H351
STOT RE 1	H372
Aquatic Acute 1	H400
Aquatic Acute 2	H401
Aquatic Chronic 2	H411

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

- : H304 – May be fatal if swallowed and enters airways.
- : H315 – Causes skin irritation.
- : H319 – Causes serious eye irritation.
- : H225 – Highly flammable liquid and vapor.
- : H226 – Flammable liquid and vapor.
- : H332 – Harmful if inhaled.
- : H335 – May cause respiratory irritation.

Weatherking® Flashing Adhesive

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: 05/13/2015

Date of issue: 06/01/2015

Precautionary Statements (GHS-US)	<p>H340 – May cause genetic defects. H350 – May cause cancer. H351 – Suspected of causing cancer. H372 – Causes damage to organs through prolonged or repeated exposure. H400 – Very toxic to aquatic life H411 – Toxic to aquatic life with long lasting effects.</p> <p>P201 – Obtain special instructions before use. P202 – Do not handle until all safety precautions have been read and understood. P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 – Keep container tightly closed. P240 – Ground/bond container and receiving equipment. P241 – Use explosion-proof electrical/ventilating/light/.../equipment. P242 – Use only non-sparking tools. P243 – Take precautionary measures against static discharge. P260 – Do not breathe dust/fumes/gas/mist/vapors/spray. P261 – Avoid breathing dust/fume/gas/mist/vapors/spray. P264 – Wash thoroughly after handling. P270 – Do not eat, drink, or smoke when using this product. P271 – Use only outdoors or in a well-ventilated area. P273 – Avoid release to the environment. P280 – Wear protective gloves/clothing/eye protection/face protection. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P308 + P313 - IF exposed or concerned: Get medical advice/attention. P332+P313 - If skin irritation occurs: Get medical advice/attention. P370 + P378 - In case of fire: Use suitable extinguishing for extinction. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.</p>
--	---

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Asphalt	(CAS No) 8052-42-4	55-65	Flam. Liq. 2, H225 Eye Irrit, 2A, H319 Carc.2, H351
Stoddard Solvent	(CAS No) 8052-41-3	20-30	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Calcium Carbonate	(CAS No) 1317-65-3	4-8	
Cellulose	(CAS No) 9004-34-6	4-8	Comb. Dust
1,3,5-trimethylbenzene	(CAS No) 108-67-8	1-2	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335

Weatherking® Flashing Adhesive

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: 05/13/2015

Date of issue: 06/01/2015

			Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Benzene, 1,2,4-trimethyl-	(CAS No) 95-63-6	1-2	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation:vapor), H332 Skin irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Quartz	(CAS No) 14808-60-7	0.1-1	Carc 1A, H350 STOT SE 3, H335 STOT RE 1, H372

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). If exposed or concerned: Get medical advice/attention.

Inhalation: When symptoms occur: go into open air and ventilate suspected area. If exposed or concerned; Get medical advice/attention.

Skin Contact: Remove contaminated clothing. Rinse affected area with water for at least 5 minutes.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.

Ingestion: Rinse mouth. Do NOT induce vomiting. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: May be fatal if swallowed and enters airways. Causes serious eye irritation. Causes skin irritation.

Indication of Immediate Medical Attention and Special Treatment Needed

General: If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use direct water stream. May spread fire.

Special Hazards Arising From the Substance or Mixture

Hazardous Combustion Products: Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and oxides of sulfur and/or nitrogen. Hydrogen sulfide and other sulfur-containing gases can evolve from this product particularly at elevated temperatures. Corrosive vapors.

Fire and Explosion Hazards: May form flammable/explosive vapor-air mixture.

Advice for Firefighters

Fire Fighting Procedures: Exercise caution when fighting any chemical fire.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Handle in accordance with good industrial hygiene and safety practice. Do not allow product to spread into the environment.

Environmental Precautions

Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and Materials for Containment and Cleaning Up

Weatherking® Flashing Adhesive

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: 05/13/2015

Date of issue: 06/01/2015

For Containment: Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material.

Methods for Cleaning Up: Collect spillage. Clear up spills immediately and dispose of waste safely.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

General Handling: Handle empty containers with care because residual vapors are flammable. Contains Sulfur, may release small amounts of hydrogen sulfide. Hydrogen sulfide is a highly flammable, explosive gas under certain conditions, is a toxic gas, and may be fatal. Gas can accumulate in the headspace of closed containers, use caution when opening sealed containers. Heating the product or containers can cause thermal decomposition of the product and release hydrogen sulfide.

Conditions for Safe Storage

General: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Store locked up.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Asphalt (8052-42-4)		
Mexico	OEL TWA (mg/m ³)	5 mg/m ³
Mexico	OEL STEL (mg/m ³)	10 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	0.5 mg/m ³
USA NOISH	NIOSH REL (ceiling) (mg/m ³)	5 mg/m ³
Ontario	OEL TWA (mg/m ³)	0.5 mg/m ³
Stoddard Solvent (8052-41-3)		
Mexico	OEL TWA (mg/m ³)	523 mg/m ³
Mexico	OEL STEL (mg/m ³)	1,050 mg/m ³
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA OSHA	OSHA PEL (TWA)(mg/m ³)	2,900 mg/m ³
USA OSHA	OSHA PEL (TWA)(ppm)	500 ppm
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	1,800 mg/m ³
USA NIOSH	NIOSH REL (TWA)(mg/m ³)	350 mg/m ³
USA IDLH	US IDLH (mg/m ³)	20,000 mg/m ³
Ontario	OEL TWA (mg/m ³)	525 mg/m ³
Calcium Carbonate (1317-65-3)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	5 mg/m ³
Cellulose (9004-34-6)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	5 mg/m ³
Ontario	OEL TWA (mg/m ³)	10 mg/m ³
1,3,5-trimethylbenzene (108-67-8)		
USA NIOSH	NIOSH REL (TWA)(ppm)	25 ppm
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	125 mg/m ³

Weatherking® Flashing Adhesive

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations


Revision Date: 05/13/2015

Date of issue: 06/01/2015

Benzene, 1,2,4-trimethyl- (95-63-6)		
USA NIOSH	NIOSH REL (TWA)(ppm)	25 ppm
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	125 mg/m ³
Quartz (14808-60-7)		
Mexico	OEL TWA (mg/m ³)	0.1 mg/m ³
USA OSHA	OSHA PEL (TWA)(mg/m ³)	250 mppcf/%SiO ₂ +5, 10 mg/m ³ %SiO ₂ +2
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	0.05 mg/m ³
Ontario	OEL TWA (mg/m ³)	0.10 mg/m ³ (designated substances regulation)

Appropriate Engineering Controls: Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Take precautionary measures against static discharges. Ensure all national/local regulations are observed. Gas detectors should be used when flammable/gases may be released.

Personal Protective Equipment: On heating: wear respiratory equipment. Protective clothing. Protective goggles. Gloves.



Hand Protection: Wear chemically resistant protective gloves

Eye Protection: Chemical goggles or safety glasses.

Skin Protection: Wear impervious gloves such as vinyl to minimize contact with skin.

Materials for Protective Clothing: Chemically resistant materials and fabrics.

Respiratory Protection: When manufacturing or handling product in large quantities and vapors or mists may be generated, maintain airborne concentrations below recommended limits. Workplace risk assessments should be completed before specifying and implementing respirator usage. NIOSH approved respirators for protection should be used if respirators are found to be necessary.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Mastic
Color	: Black
Odor	: Petroleum distillates
Odor Threshold	: Not applicable
pH	: Not applicable
Melting Point	: No test data available
Freezing Point	: No test data available
Boiling Point (760 mm Hg)	: 300-390°F (149-199°C)
Flash Point – Closed Cup	: 105°F (41°C)
Evaporation Rate (Butyl Acetate = 1)	: No test data available
Flammability (solid, gas)	: Not applicable
Flammability Limits in Air	: Lower: No test data available; Upper: No test data available
Vapor Pressure	: 5 mmHg
Vapor Density (Air = 1)	: 3.9-4.3 @ Air=1
Specific Gravity (H₂O = 1)	: 0.90

Weatherking® Flashing Adhesive

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: 05/13/2015

Date of issue: 06/01/2015

Solubility in Water (by wt)	:	Insoluble
Explosive Properties	:	Lower limit: 0.8% Upper Limit: 6.0%
% Volatile	:	27-30%
VOC	:	250 g/L

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

Chemical Stability: Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

Possibility of Hazardous Reactions: Will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). May release flammable gases. Contains a small amount of hydrogen sulfide. Hydrogen sulfide is a fatal, and highly flammable gas with a rotten egg odor that quickly causes odor fatigue. Heating of this product and storage under elevated temperatures or over long periods of time may release higher amounts of hydrogen sulfide. Hydrogen sulfide is also an asphyxiant.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on Toxicological Effects – Product

Acute Toxicity: Not classified.

LD50 and LC50 Data: Not available.

Skin Corrosion/Irritation: Not available.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: No data available.

Teratogenicity: No data available.

Carcinogenicity: May cause cancer (inhalation).

Specific Target Organ Toxicity (Repeated Exposure): May cause damage to organs through prolonged or repeated exposure.

Reproductive Toxicity: No relevant data found.

Specific Target Organ Toxicity (Single Exposure): Not classified.

Aspiration Hazard: May be fatal if swallowed and enters airways.

Symptoms/Injuries After Inhalation: May cause cancer by inhalation.

Symptoms/injuries after Skin Contact: Causes skin irritation.

Symptoms/injuries after Eye Contact: Causes serious eye irritation.

Symptoms/Injuries After Ingestion: may be fatal if swallowed and enters airways.

Chronic Symptoms: May cause genetic defects. May cause cancer.

Information on Toxicological Effects – Ingredient(s)

LD50 and LC50 Data:

Asphalt (8052-42-4)	
LD50, Oral Rat	> 5,000 mg/kg
LD50, Dermal Rabbit	> 2,000 mg/kg
IARC Group	2B
National Toxicity Program Status	Twelfth Report – Items under consideration.

Stoddard Solvent (8052-41-3)	
LD50, Oral Rat	> 5 mg/kg
LD50, Dermal Rabbit	> 3 mg/kg
Benzene, 1,2,4-trimethyl- (95-63-6)	
LD50, Oral Rat	6,000 mg/kg
LD50, Dermal Rabbit	> 3,160 mg/kg
LC50, Inhalation Rat (mg/L)	18 g/m ³ (Exposure time: 4 h)

Weatherking® Flashing Adhesive

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: 05/13/2015

Date of issue: 06/01/2015

1,3,5-trimethylbenzene (108-67-8)	
LC50, Inhalation rat (mg/L)	24 g/m ³ (Exposure time: 4 h)
Quartz (14808-60-7)	
LD50, Oral Rat	> 5,000 mg/kg
IARC Group	1
National Toxicity Program (NTP) Status	Known Human Carcinogens.
Cellulose (9004-34-6)	
LC50, Inhalation Rat (mg/L)	>5,800 mg/m ³ (Exposure time: 4 h)
LD50, Dermal Rabbit	> 2,000 mg/kg
Aluminum Hydroxide (Al(OH)₃) (21645-51-2)	
LD50, Oral Rat	6,000 mg/kg
Attipulgite (12174-11-7)	
IARC Group	2B, 3

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology – General: Very toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Persistence and Degradability

Not established. May cause long-term adverse effects in the environment.

Mobility in Soil

Mobility in Soil: Not available. Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

Unused and Contaminated Product: Preferred option includes sending to a licensed, permitted: Recycler, Reclaimer, Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, SDS Section 7; Stability & Reactivity Information, SDS Section 10; Regulatory Information, SDS Section 15.

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : Tars, liquid – NOT
REGULATED NON BULK

Hazard Class : 3

Identification Number : UN1999

Packing Group : III

14.2 In Accordance with IMDG

Proper Shipping Name : Tars, liquid

Hazard Class : 3

Identification Number : UN1999

EmS No. : F-E, S-E

Packing Group : III

14.3 In Accordance with IATA

Proper Shipping Name

Hazard Class

Weatherking® Flashing Adhesive

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: 05/13/2015

Date of issue: 06/01/2015

Identification Number	:	Tars, liquid
Packing Group	:	3
ERG Code	:	UN1999
	:	III
	:	3L

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Asphalt (8052-42-4)	
Listed on the United States, TSCA (Toxic Substances Control Act)	
Benzene, 1,2,4-trimethyl- (95-63-6)	
Listed on the United States, TSCA (Toxic Substances Control Act)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 313 – Emission Reporting	1.0%
Stoddard Solvent(8052-41-3)	
Listed on the United States, TSCA (Toxic Substances Control Act)	
1,3,5-trimethylbenzene (108-67-8)	
Listed on the United States, TSCA (Toxic Substances Control Act)	
EPA TSCA Regulatory Flag	T – T – indicates a substance that is the subject of a Section 4 test rule under TSCA.
Quartz (14808-60-7)	
Listed on the United States, TSCA (Toxic Substances Control Act)	
Cellulose (9004-34-6)	
Listed on the United States, TSCA (Toxic Substances Control Act)	
Aluminum hydroxide (Al(OH)₃ (21645-51-2)	
Listed on the United States, TSCA (Toxic Substances Control Act)	
Calcium Carbonate (1317-65-3)	
Listed on the United States, TSCA (Toxic Substances Control Act)	

US State Regulations

Quartz (14808-60-7)	
U.S. – California – Proposition 65 – Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Attapulgate (12174-11-7)	
U.S. – California – Proposition 65 – Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Asphalt (8052-42-4)	
RTK – U.S. – Massachusetts – Right To Know List	



Weatherking® Flashing Adhesive

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations
 Revision Date: 05/13/2015 Date of issue: 06/01/2015

RTK – U.S. – New Jersey – Right to Know Hazardous Substance List RTK – U.S. – Pennsylvania – RTK (Right to Know) List
Benzene, 1,2,4-trimethyl- (95-63-6)
RTK – U.S. – Massachusetts – Right To Know List RTK – U.S. – New Jersey – Right to Know Hazardous Substance List RTK – U.S. – Pennsylvania – RTK (Right to Know) – Environmental hazard List RTK – U.S. – Pennsylvania – RTK (Right to Know) List
Stoddard Solvent (8052-41-3)
RTK – U.S. – Massachusetts – Right To Know List RTK – U.S. – New Jersey – Right to Know Hazardous Substance List RTK – U.S. – Pennsylvania – RTK (Right to Know) List
1,3,5-trimethylbenzene (108-67-8)
RTK – U.S. – Massachusetts – Right To Know List
Quartz (14808-60-7)
RTK – U.S. – Massachusetts – Right To Know List RTK – U.S. – New Jersey – Right to Know Hazardous Substance List RTK – U.S. – Pennsylvania – RTK (Right to Know) List
Cellulose (9004-34-6)
RTK – U.S. – Massachusetts – Right To Know List RTK – U.S. – New Jersey – Right to Know Hazardous Substance List RTK – U.S. – Pennsylvania – RTK (Right to Know) List
Calcium Carbonate (1317-65-3)
RTK – U.S. – Massachusetts – Right To Know List RTK – U.S. – New Jersey – Right to Know Hazardous Substance List RTK – U.S. – Pennsylvania – RTK (Right to Know) List

Canadian Regulations

Weatherking® Flashing Adhesive	
WHMIS Classification	Class B Division 3 – Combustible Liquid Class D Division 2 Subdivision A – Very toxic material causing other toxic effects. Class D Division 2 Subdivision B – Toxic material causing other toxic effects.
 	
Asphalt (8052-42-4)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
Benzene, 1,2,4-trimethyl- (95-63-6)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List.	
WHMIS Classification	Class B Division 3 – Combustible Liquid

Weatherking® Flashing Adhesive

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Revision Date: 05/13/2015

Date of issue: 06/01/2015

	Class D Division 2 Subdivision A – Very toxic material causing other toxic effects. Class D Division 2 Subdivision B – Toxic material causing other toxic effects.
Stoddard Solvent (8052-41-3)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List.	
WHMIS Classification	Class B Division 3 – Combustible Liquid Class D Division 2 Subdivision B – Toxic material causing other toxic effects.
1,3,5-trimethylbenzene (108-67-8)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List.	
WHMIS Classification	Class B Division 3 – Combustible Liquid
Quartz (14808-60-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory. Listed on the Canadian Ingredient Disclosure List.	
WHMIS Classification	Class D Division 2 Subdivision A – Very toxic material causing other toxic effects.
Cellulose (9004-34-6)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria.
Calcium Carbonate (1317-65-3)	
Listed on the Canadian NDSL (Non-Domestic Substances List) inventory.	
WHMIS Classification	Class D Division 2 Subdivision A – Very toxic material causing other toxic effects.
This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.	

SECTION 16: OTHER INFORMATION

Revision Date	: 05/13/2015
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.
Party Responsible for the Preparation of This Document	: The Garland Company, Inc. 3800 East 91 st Street Cleveland, Ohio 44105-2197 T-1800-762-8225 F-216-641-0633

This information is based on our knowledge as of the Revision Date and is intended to describe the product only for the purposes of health, safety and environmental requirements as of the Revision Date. It should not therefore be construed as guaranteeing any specific property of the product nor as providing any warranty, expressed or implied. The user assumes all responsibility, liability, risk of loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use, or disposal of the product.

North America GHS US 2015 & WHMIS