



# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Revision Date: 10/06/2014 Date of issue: 06/01/2015

Version: 1.0

### SECTION 1: IDENTIFICATION

#### Product Identifier

**Product Form:** Mixture

**Product Name:** White-Knight® Dark Gray

**Product Code:** 7831

#### Intended Use of the Product

Urethane roof coating. For professional use only.

#### Name, Address, and Telephone of the Responsible Party

##### **Manufacturer**

The Garland Company, Inc.  
3800 East 91st Street  
Cleveland, Ohio 44105-2197  
T-800-762-8225  
F-216-641-0633

[www.garlandco.com](http://www.garlandco.com)

##### **Emergency Telephone Number**

**Emergency number** : 1-800-262-8200 (CHEMTREC)

##### **Supplier**

The Garland Company, Inc.  
3800 East 91st Street  
Cleveland, Ohio 44105-2197  
T-800-762-8225  
F-216-641-0633

[www.garlandco.com](http://www.garlandco.com)

### SECTION 2: HAZARDS IDENTIFICATION

#### Classification of the Substance or Mixture

##### **Classification (GHS-US)**

|                                     |      |
|-------------------------------------|------|
| Flam. Liq. 3                        | H226 |
| Acute Tox. 3 (Inhalation:dust,mist) | H331 |
| Skin Irrit. 2                       | H315 |
| Eye Irrit. 2A                       | H319 |
| Resp. Sens. 1                       | H334 |
| Skin Sens. 1                        | H317 |
| Muta. 1B                            | H340 |
| Carc. 1A                            | H350 |
| Repr. 1B                            | H360 |
| Asp. Tox. 1                         | H304 |
| Aquatic Acute 3                     | H402 |
| Aquatic Chronic 3                   | H412 |

#### Label Elements

##### **GHS-US Labeling**

##### **Hazard Pictograms (GHS-US)**



##### **Signal Word (GHS-US)**

: Danger

##### **Hazard Statements (GHS-US)**

: H226 - Flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H331 - Toxic if inhaled  
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled  
H340 - May cause genetic defects  
H350 - May cause cancer  
H360 - May damage fertility or the unborn child

# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Precautionary Statements (GHS-US) :**
- H402 - Harmful to aquatic life
  - H412 - Harmful to aquatic life with long lasting effects
  - P201 - Obtain special instructions before use
  - P202 - Do not handle until all safety precautions have been read and understood
  - P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
  - P233 - Keep container tightly closed
  - P240 - Ground/bond container and receiving equipment
  - P241 - Use explosion-proof electrical, lighting, ventilating equipment
  - P242 - Use only non-sparking tools
  - P243 - Take precautionary measures against static discharge
  - P260 - Do not breathe mist, spray, vapors
  - P264 - Wash hands, forearms, and exposed areas thoroughly after handling
  - P271 - Use only outdoors or in a well-ventilated area
  - P272 - Contaminated work clothing should not be allowed out of the workplace
  - P273 - Avoid release to the environment
  - P280 - Wear eye protection, face protection, protective clothing, protective gloves
  - P284 - Wear respiratory protection
  - P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
  - P302+P352 - IF ON SKIN: Wash with plenty of soap and water
  - P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
  - P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing
  - P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
  - P308+P313 - If exposed or concerned: Get medical advice/attention
  - P310 - Immediately call a POISON CENTER or doctor/physician
  - P320 - Specific treatment is urgent (see Section 4)
  - P331 - If swallowed, do NOT induce vomiting
  - P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
  - P337+P313 - If eye irritation persists: Get medical advice/attention
  - P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician
  - P362 - Take off contaminated clothing and wash before reuse
  - P362+P364 - Take off contaminated clothing and wash it before reuse
  - P370+P378 - In case of fire: Use appropriate media for extinction
  - P403+P233 - Store in a well-ventilated place. Keep container tightly closed
  - P235 - Keep cool
  - P405 - Store locked up
  - P501 - Dispose of contents/container according to local, regional, national, and international regulations

### Other Hazards

**Other Hazards Not Contributing to the Classification:** Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

**Unknown Acute Toxicity (GHS-US)** Not available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Mixture

| Name                                   | Product identifier  | % (w/w) | Classification (GHS-US)   |
|--|---------------------|---------|---|
| Naphtha, petroleum, hydrotreated heavy | (CAS No) 64742-48-9 | 7 - 13  | Flam. Liq. 3, H226<br>Skin Irrit. 2, H315<br>Muta. 1B, H340<br>Carc. 1B, H350 |

# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|   |                      |         |  |
|---|----------------------|---------|--|
|   |                      |         | Repr. 2, H361<br>STOT SE 3, H336<br>Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411   |
| Talc  | (CAS No) 14807-96-6  | 5 - 10  | Comb. Dust   |
| Titanium dioxide  | (CAS No) 13463-67-7  | 5 - 10  | Skin Irrit. 2, H315  |
| Toluene-2,4-diisocyanate  | (CAS No) 584-84-9    | 3 - 7   | Acute Tox. 1 (Inhalation:dust,mist), H330<br>Skin Irrit. 2, H315<br>Eye Irrit. 2A, H319<br>Resp. Sens. 1A, H334<br>Skin Sens. 1, H317<br>Carc. 2, H351<br>STOT SE 3, H335<br>Aquatic Chronic 3, H412 |
| Silicic acid, aluminum sodium salt  | (CAS No) 1344-00-9   | 3 - 7   | Aquatic Acute 3, H402  |
| Propane, oxybis(methoxy-  | (CAS No) 111109-77-4 | 1 - 5   | Eye Irrit. 2A, H319  |
| Isophorone diisocyanate   | (CAS No) 4098-71-9   | 1 - 3   | Acute Tox. 4 (Oral), H302<br>Acute Tox. 2 (Inhalation:dust,mist), H330   |
| Magnesium carbonate   | (CAS No) 546-93-0    | 1 - 3   | Comb. Dust   |
| Toluene 2,6-diisocyanate  | (CAS No) 91-08-7     | 1 - 2   | Acute Tox. 2 (Inhalation), H330<br>Skin Irrit. 2, H315<br>Eye Irrit. 2A, H319<br>Resp. Sens. 1, H334<br>Skin Sens. 1, H317<br>Carc. 2, H351<br>STOT SE 3, H335                                       |
| Bis(2-ethylhexyl) adipate   | (CAS No) 103-23-1    | 1 - 2   | Aquatic Acute 1, H400  |
| Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate   | (CAS No) 41556-26-7  | 0.1 - 1 | Flam. Liq. 4, H227<br>Skin Sens. 1, H317<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410   |
| 2,6-Di-tert-butyl-p-cresol  | (CAS No) 128-37-0    | 0.1 - 1 | Acute Tox. 4 (Oral), H302<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410  |
| Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]- | (CAS No) 104810-47-1 | 0.1 - 1 | Skin Sens. 1, H317<br>Aquatic Chronic 2, H411  |
| Quartz  | (CAS No) 14808-60-7  | 0.1 - 1 | Carc. 1A, H350<br>STOT SE 3, H335<br>STOT RE 1, H372   |
| Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-   | (CAS No) 104810-48-2 | 0.1 - 1 | Skin Sens. 1, H317<br>Aquatic Chronic 2, H411  |
| Dibutyltin dilaurate  | (CAS No) 77-58-7     | 0.1 - 1 | Acute Tox. 3 (Dermal), H311<br>Skin Corr. 1C, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Muta. 2, H341<br>Repr. 1B, H360  |

# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |                     |       |  |
|--|---------------------|-------|--|
|  |                     |       | STOT SE 1, H370<br>STOT RE 1, H372<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410 |
| 1,4-Diazabicyclo[2.2.2]octane                                      | (CAS No) 280-57-9   | 0.099 | Acute Tox. 4 (Oral), H302  |
| Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester | (CAS No) 82919-37-7 | 0.06  | Skin Sens. 1, H317<br>Aquatic Acute 1, H400<br>Aquatic Chronic 1, H410                 |

## SECTION 4: FIRST AID MEASURES

### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

**Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.

**Skin Contact:** Rinse immediately with plenty of water. Obtain medical attention if irritation develops or persists. Wash contaminated clothing before reuse.

**Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

### Most Important Symptoms and Effects Both Acute and Delayed

**General:** May damage fertility or the unborn child. May cause genetic defects. Eye irritation. Toxic if inhaled. Causes skin irritation. May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause cancer. May be fatal if swallowed and enters airways.

**Inhalation:** May cause allergy or asthma symptoms or breathing difficulties if inhaled. Toxic if inhaled.

**Skin Contact:** Causes skin irritation. May cause an allergic skin reaction.

**Eye Contact:** Causes serious eye irritation.

**Ingestion:** May be fatal if swallowed and enters airways.

**Chronic Symptoms:** None expected under normal conditions of use.

### Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

## SECTION 5: FIRE-FIGHTING MEASURES

### Extinguishing Media

**Suitable Extinguishing Media:** Use extinguishing media appropriate for surrounding fire.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Flammable liquid and vapor.

**Explosion Hazard:** May form flammable/explosive vapor-air mixture.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Not available

**Other information:** Refer to Section 9 for flammability properties.

### Reference to Other Sections

Refer to section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray). Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

### For Emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Stop leak if safe to do so. Eliminate ignition sources. Ventilate area.

### Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### Reference to Other Sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: HANDLING AND STORAGE

### Precautions for Safe Handling

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers.

**Storage Area:** Store locked up. Store in a well-ventilated place. Keep cool.

**Special Rules on Packaging:** Keep only in original container.

### Specific End Use(s)

Urethane roof coating. For professional use only.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

| <b>Quartz (14808-60-7)</b> |                                      |   |
|----------------------------|--------------------------------------|---|
| Mexico                     | OEL TWA (mg/m <sup>3</sup> )         | 0.1 mg/m <sup>3</sup>   |
| USA ACGIH                  | ACGIH TWA (mg/m <sup>3</sup> )       | 0.025 mg/m <sup>3</sup>   |
| USA OSHA                   | OSHA PEL (STEL) (mg/m <sup>3</sup> ) | 250 mppcf/%SiO <sub>2</sub> +5, 10mg/m <sup>3</sup> /%SiO <sub>2</sub> +2 |
| USA NIOSH                  | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 0.05 mg/m <sup>3</sup>  |
| USA IDLH                   | US IDLH (mg/m <sup>3</sup> )         | 50 mg/m <sup>3</sup>  |
| Alberta                    | OEL TWA (mg/m <sup>3</sup> )         | 0.025 mg/m <sup>3</sup>   |
| British Columbia           | OEL TWA (mg/m <sup>3</sup> )         | 0.025 mg/m <sup>3</sup>   |
| Manitoba                   | OEL TWA (mg/m <sup>3</sup> )         | 0.025 mg/m <sup>3</sup>   |
| New Brunswick              | OEL TWA (mg/m <sup>3</sup> )         | 0.1 mg/m <sup>3</sup>   |
| Newfoundland & Labrador    | OEL TWA (mg/m <sup>3</sup> )         | 0.025 mg/m <sup>3</sup>   |
| Nova Scotia                | OEL TWA (mg/m <sup>3</sup> )         | 0.025 mg/m <sup>3</sup>   |
| Nunavut                    | OEL TWA (mg/m <sup>3</sup> )         | 0.3 mg/m <sup>3</sup> (total mass)  |
| Northwest Territories      | OEL TWA (mg/m <sup>3</sup> )         | 0.3 mg/m <sup>3</sup> (total mass)  |
| Ontario                    | OEL TWA (mg/m <sup>3</sup> )         | 0.10 mg/m <sup>3</sup> (designated substances regulation)                 |
| Prince Edward Island       | OEL TWA (mg/m <sup>3</sup> )         | 0.025 mg/m <sup>3</sup>   |
| Québec                     | VEMP (mg/m <sup>3</sup> )            | 0.1 mg/m <sup>3</sup>   |
| Saskatchewan               | OEL TWA (mg/m <sup>3</sup> )         | 0.05 mg/m <sup>3</sup>  |
| Yukon                      | OEL TWA (mg/m <sup>3</sup> )         | 300 particle/mL   |

# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>2,6-Di-tert-butyl-p-cresol (128-37-0)</b> |                                      |   |
|--|--------------------------------------|---|
| Mexico                                       | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| Mexico                                       | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>  |
| USA ACGIH                                    | ACGIH TWA (mg/m <sup>3</sup> )       | 2 mg/m <sup>3</sup>   |
| USA NIOSH                                    | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 10 mg/m <sup>3</sup>  |
| Alberta                                      | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| British Columbia                             | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>   |
| Manitoba                                     | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>   |
| New Brunswick                                | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| Newfoundland & Labrador                      | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>   |
| Nova Scotia                                  | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>   |
| Nunavut                                      | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>  |
| Nunavut                                      | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| Northwest Territories                        | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>  |
| Northwest Territories                        | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| Ontario                                      | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>   |
| Prince Edward Island                         | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>   |
| Québec                                       | VECD (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup>  |
| Saskatchewan                                 | OEL STEL (mg/m <sup>3</sup> )        | 4 mg/m <sup>3</sup>   |
| Saskatchewan                                 | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>   |
| Yukon  | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>  |
| Yukon  | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| <b>Aluminum oxide (1344-28-1)</b>            |                                      |   |
| Mexico                                       | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| USA OSHA                                     | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 5 mg/m <sup>3</sup>   |
| Alberta                                      | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| New Brunswick                                | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| Nunavut                                      | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>  |
| Nunavut                                      | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup> (total mass)   |
| Northwest Territories                        | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>  |
| Northwest Territories                        | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup> (total mass)   |
| Québec                                       | VEMP (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica)            |
| Saskatchewan                                 | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>  |
| Saskatchewan                                 | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| Yukon  | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup> (Al <sub>2</sub> O <sub>3</sub> )                              |
| Yukon  | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup> (Al <sub>2</sub> O <sub>3</sub> )                              |
| <b>Limestone (1317-65-3)</b>                 |                                      |   |
| Mexico                                       | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| Mexico                                       | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>  |
| USA OSHA                                     | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 5 mg/m <sup>3</sup>   |
| USA NIOSH                                    | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 5 mg/m <sup>3</sup>   |
| Alberta                                      | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| British Columbia                             | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>  |
| British Columbia                             | OEL TWA (mg/m <sup>3</sup> )         | 3 mg/m <sup>3</sup>   |
| New Brunswick                                | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>  |
| Nunavut                                      | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup> (total mass)   |
| Northwest Territories                        | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup> (total mass)   |
| Québec                                       | VEMP (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup> (Limestone, containing no Asbestos and <1% Crystalline silica) |
| Saskatchewan                                 | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>  |

# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|   |   |  |
|---|---|--|
| Saskatchewan  | OEL TWA (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup>   |
| Yukon   | OEL STEL (mg/m <sup>3</sup> )           | 20 mg/m <sup>3</sup>   |
| Yukon   | OEL TWA (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup>   |
| <b>Silica gel, precipitated, crystalline free (112926-00-8)</b> |   |  |
| Mexico  | OEL TWA (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup>   |
| British Columbia  | OEL TWA (mg/m <sup>3</sup> )            | 1.5 mg/m <sup>3</sup>  |
| New Brunswick   | OEL TWA (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup>   |
| Ontario   | OEL TWA (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup>   |
| Québec  | VEMP (mg/m <sup>3</sup> )               | 6 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica)                        |
| Saskatchewan  | OEL STEL (mg/m <sup>3</sup> )           | 20 mg/m <sup>3</sup>   |
| Saskatchewan  | OEL TWA (mg/m <sup>3</sup> )            | 10 mg/m <sup>3</sup>   |
| <b>Toluene-2,4-diisocyanate (584-84-9)</b>                      |   |  |
| Mexico  | OEL TWA (mg/m <sup>3</sup> )            | 0.14 mg/m <sup>3</sup>   |
| Mexico  | OEL TWA (ppm)                           | 0.02 ppm   |
| USA ACGIH   | ACGIH TWA (ppm)                         | 0.005 ppm  |
| USA ACGIH   | ACGIH STEL (ppm)                        | 0.02 ppm   |
| USA OSHA  | OSHA PEL (Ceiling) (mg/m <sup>3</sup> ) | 0.14 mg/m <sup>3</sup>   |
| USA OSHA  | OSHA PEL (Ceiling) (ppm)                | 0.02 ppm   |
| USA IDLH  | US IDLH (ppm)                           | 2.5 ppm  |
| Alberta   | OEL Ceiling (mg/m <sup>3</sup> )        | 0.1 mg/m <sup>3</sup>  |
| Alberta   | OEL Ceiling (ppm)                       | 0.02 ppm   |
| Alberta   | OEL TWA (mg/m <sup>3</sup> )            | 0.04 mg/m <sup>3</sup>   |
| Alberta   | OEL TWA (ppm)                           | 0.005 ppm  |
| British Columbia  | OEL Ceiling (ppm)                       | 0.01 ppm   |
| British Columbia  | OEL TWA (ppm)                           | 0.005 ppm  |
| Manitoba  | OEL STEL (ppm)                          | 0.02 ppm   |
| Manitoba  | OEL TWA (ppm)                           | 0.005 ppm  |
| New Brunswick   | OEL STEL (mg/m <sup>3</sup> )           | 0.14 mg/m <sup>3</sup>   |
| New Brunswick   | OEL STEL (ppm)                          | 0.02 ppm   |
| New Brunswick   | OEL TWA (mg/m <sup>3</sup> )            | 0.036 mg/m <sup>3</sup>  |
| New Brunswick   | OEL TWA (ppm)                           | 0.005 ppm  |
| Newfoundland & Labrador   | OEL STEL (ppm)                          | 0.02 ppm   |
| Newfoundland & Labrador   | OEL TWA (ppm)                           | 0.005 ppm  |
| Nova Scotia   | OEL STEL (ppm)                          | 0.02 ppm   |
| Nova Scotia   | OEL TWA (ppm)                           | 0.005 ppm  |
| Nunavut   | OEL Ceiling (mg/m <sup>3</sup> )        | 0.14 mg/m <sup>3</sup>   |
| Nunavut   | OEL Ceiling (ppm)                       | 0.02 ppm   |
| Northwest Territories   | OEL Ceiling (mg/m <sup>3</sup> )        | 0.14 mg/m <sup>3</sup>   |
| Northwest Territories   | OEL Ceiling (ppm)                       | 0.02 ppm   |
| Ontario   | OEL Ceiling (ppm)                       | 0.02 ppm (designated substances regulation)  |
| Ontario   | OEL STEL (ppm)                          | 0.02 ppm   |
| Ontario   | OEL TWA (ppm)                           | 0.005 ppm (applies to workplaces to which the designated substances regulation does not apply) |
| Prince Edward Island  | OEL STEL (ppm)                          | 0.02 ppm   |
| Prince Edward Island  | OEL TWA (ppm)                           | 0.005 ppm  |
| Saskatchewan  | OEL STEL (ppm)                          | 0.02 ppm   |
| Saskatchewan  | OEL TWA (ppm)                           | 0.005 ppm  |
| Yukon   | OEL Ceiling (mg/m <sup>3</sup> )        | 0.14 mg/m <sup>3</sup>   |
| Yukon   | OEL Ceiling (ppm)                       | 0.02 ppm   |

# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| <b>Toluene 2,6-diisocyanate (91-08-7)</b> |                                      |  |
|---|--------------------------------------|--|
| USA ACGIH                                 | ACGIH TWA (ppm)                      | 0.005 ppm  |
| USA ACGIH                                 | ACGIH STEL (ppm)                     | 0.02 ppm   |
| Alberta                                   | OEL Ceiling (mg/m <sup>3</sup> )     | 0.1 mg/m <sup>3</sup>  |
| Alberta                                   | OEL Ceiling (ppm)                    | 0.02 ppm   |
| Alberta                                   | OEL TWA (mg/m <sup>3</sup> )         | 0.04 mg/m <sup>3</sup>   |
| Alberta                                   | OEL TWA (ppm)                        | 0.005 ppm  |
| British Columbia                          | OEL Ceiling (ppm)                    | 0.01 ppm   |
| British Columbia                          | OEL TWA (ppm)                        | 0.005 ppm  |
| Manitoba                                  | OEL STEL (ppm)                       | 0.02 ppm   |
| Manitoba                                  | OEL TWA (ppm)                        | 0.005 ppm  |
| Newfoundland & Labrador                   | OEL STEL (ppm)                       | 0.02 ppm   |
| Newfoundland & Labrador                   | OEL TWA (ppm)                        | 0.005 ppm  |
| Nova Scotia                               | OEL STEL (ppm)                       | 0.02 ppm   |
| Nova Scotia                               | OEL TWA (ppm)                        | 0.005 ppm  |
| Ontario                                   | OEL Ceiling (ppm)                    | 0.02 ppm (designated substances regulation)  |
| Ontario                                   | OEL STEL (ppm)                       | 0.02 ppm   |
| Ontario                                   | OEL TWA (ppm)                        | 0.005 ppm (applies to workplaces to which the designated substances regulation does not apply) |
| Prince Edward Island                      | OEL STEL (ppm)                       | 0.02 ppm   |
| Prince Edward Island                      | OEL TWA (ppm)                        | 0.005 ppm  |
| Saskatchewan                              | OEL STEL (ppm)                       | 0.02 ppm   |
| Saskatchewan                              | OEL TWA (ppm)                        | 0.005 ppm  |
| <b>Talc (14807-96-6)</b>                  |                                      |  |
| Mexico                                    | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>  |
| USA ACGIH                                 | ACGIH TWA (mg/m <sup>3</sup> )       | 2 mg/m <sup>3</sup>  |
| USA NIOSH                                 | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 2 mg/m <sup>3</sup> (containing no Asbestos and <1% Quartz)                                    |
| USA IDLH                                  | US IDLH (mg/m <sup>3</sup> )         | 1000 mg/m <sup>3</sup> (containing no asbestos and <1% quartz)                                 |
| Alberta                                   | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>  |
| British Columbia                          | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup> (particulate matter containing no Asbestos and <1% Crystalline silica)     |
| Manitoba                                  | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>  |
| New Brunswick                             | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>  |
| Newfoundland & Labrador                   | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>  |
| Nova Scotia                               | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>  |
| Nunavut                                   | OEL TWA (mg/m <sup>3</sup> )         | 6 mg/m <sup>3</sup> (total mass)   |
| Northwest Territories                     | OEL TWA (mg/m <sup>3</sup> )         | 6 mg/m <sup>3</sup> (total mass)   |
| Ontario                                   | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica)                        |
| Prince Edward Island                      | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup> (particulate matter containing no Asbestos and <1% Crystalline silica)     |
| Québec                                    | VEMP (mg/m <sup>3</sup> )            | 3 mg/m <sup>3</sup>  |
| Saskatchewan                              | OEL TWA (mg/m <sup>3</sup> )         | 2 mg/m <sup>3</sup>  |
| Yukon                                     | OEL TWA (mg/m <sup>3</sup> )         | 20 mppcf   |
| <b>Magnesium carbonate (546-93-0)</b>     |                                      |  |
| Mexico                                    | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>   |
| Mexico                                    | OEL STEL (mg/m <sup>3</sup> )        | 20 mg/m <sup>3</sup>   |
| USA OSHA                                  | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 5 mg/m <sup>3</sup>  |
| USA NIOSH                                 | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 5 mg/m <sup>3</sup>  |
| British Columbia                          | OEL TWA (mg/m <sup>3</sup> )         | 3 mg/m <sup>3</sup>  |
| New Brunswick                             | OEL TWA (mg/m <sup>3</sup> )         | 10 mg/m <sup>3</sup>   |



# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |                                       |  |
|--|---------------------------------------|--|
| Ontario                                    | OEL TWA (mg/m <sup>3</sup> )          | 10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica) |
| Québec                                     | VEMP (mg/m <sup>3</sup> )             | 10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica) |
| Saskatchewan                               | OEL STEL (mg/m <sup>3</sup> )         | 20 mg/m <sup>3</sup>   |
| Saskatchewan                               | OEL TWA (mg/m <sup>3</sup> )          | 10 mg/m <sup>3</sup>   |
| <b>Titanium dioxide (13463-67-7)</b>       |                                       |  |
| Mexico                                     | OEL TWA (mg/m <sup>3</sup> )          | 10 mg/m <sup>3</sup>   |
| Mexico                                     | OEL STEL (mg/m <sup>3</sup> )         | 20 mg/m <sup>3</sup>   |
| USA ACGIH                                  | ACGIH TWA (mg/m <sup>3</sup> )        | 10 mg/m <sup>3</sup>   |
| USA OSHA                                   | OSHA PEL (TWA) (mg/m <sup>3</sup> )   | 15 mg/m <sup>3</sup>   |
| USA IDLH                                   | US IDLH (mg/m <sup>3</sup> )          | 5000 mg/m <sup>3</sup>   |
| Alberta                                    | OEL TWA (mg/m <sup>3</sup> )          | 10 mg/m <sup>3</sup>   |
| British Columbia                           | OEL TWA (mg/m <sup>3</sup> )          | 3 mg/m <sup>3</sup>  |
| Manitoba                                   | OEL TWA (mg/m <sup>3</sup> )          | 10 mg/m <sup>3</sup>   |
| New Brunswick                              | OEL TWA (mg/m <sup>3</sup> )          | 10 mg/m <sup>3</sup>   |
| Newfoundland & Labrador                    | OEL TWA (mg/m <sup>3</sup> )          | 10 mg/m <sup>3</sup>   |
| Nova Scotia                                | OEL TWA (mg/m <sup>3</sup> )          | 10 mg/m <sup>3</sup>   |
| Nunavut                                    | OEL TWA (mg/m <sup>3</sup> )          | 10 mg/m <sup>3</sup> (total mass)  |
| Northwest Territories                      | OEL TWA (mg/m <sup>3</sup> )          | 10 mg/m <sup>3</sup> (total mass)  |
| Ontario                                    | OEL TWA (mg/m <sup>3</sup> )          | 10 mg/m <sup>3</sup>   |
| Prince Edward Island                       | OEL TWA (mg/m <sup>3</sup> )          | 10 mg/m <sup>3</sup>   |
| Québec                                     | VEMP (mg/m <sup>3</sup> )             | 10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica) |
| Saskatchewan                               | OEL STEL (mg/m <sup>3</sup> )         | 20 mg/m <sup>3</sup>   |
| Saskatchewan                               | OEL TWA (mg/m <sup>3</sup> )          | 10 mg/m <sup>3</sup>   |
| Yukon                                      | OEL STEL (mg/m <sup>3</sup> )         | 20 mg/m <sup>3</sup>   |
| Yukon                                      | OEL TWA (mg/m <sup>3</sup> )          | 10 mg/m <sup>3</sup>   |
| <b>Isophorone diisocyanate (4098-71-9)</b> |                                       |  |
| Mexico                                     | OEL TWA (mg/m <sup>3</sup> )          | 0.09 mg/m <sup>3</sup>   |
| Mexico                                     | OEL TWA (ppm)                         | 0.01 ppm   |
| USA ACGIH                                  | ACGIH TWA (ppm)                       | 0.005 ppm  |
| USA NIOSH                                  | NIOSH REL (TWA) (mg/m <sup>3</sup> )  | 0.045 mg/m <sup>3</sup>  |
| USA NIOSH                                  | NIOSH REL (TWA) (ppm)                 | 0.005 ppm  |
| USA NIOSH                                  | NIOSH REL (STEL) (mg/m <sup>3</sup> ) | 0.180 mg/m <sup>3</sup>  |
| USA NIOSH                                  | NIOSH REL (STEL) (ppm)                | 0.02 ppm   |
| Alberta                                    | OEL TWA (mg/m <sup>3</sup> )          | 0.05 mg/m <sup>3</sup>   |
| Alberta                                    | OEL TWA (ppm)                         | 0.005 ppm  |
| British Columbia                           | OEL Ceiling (ppm)                     | 0.01 ppm   |
| British Columbia                           | OEL TWA (ppm)                         | 0.005 ppm  |
| Manitoba                                   | OEL TWA (ppm)                         | 0.005 ppm  |
| New Brunswick                              | OEL TWA (mg/m <sup>3</sup> )          | 0.045 mg/m <sup>3</sup>  |
| New Brunswick                              | OEL TWA (ppm)                         | 0.005 ppm  |
| Newfoundland & Labrador                    | OEL TWA (ppm)                         | 0.005 ppm  |
| Nova Scotia                                | OEL TWA (ppm)                         | 0.005 ppm  |
| Nunavut                                    | OEL STEL (mg/m <sup>3</sup> )         | 0.27 mg/m <sup>3</sup>   |
| Nunavut                                    | OEL STEL (ppm)                        | 0.03 ppm   |
| Nunavut                                    | OEL TWA (mg/m <sup>3</sup> )          | 0.09 mg/m <sup>3</sup>   |
| Nunavut                                    | OEL TWA (ppm)                         | 0.01 ppm   |
| Northwest Territories                      | OEL STEL (mg/m <sup>3</sup> )         | 0.27 mg/m <sup>3</sup>   |
| Northwest Territories                      | OEL STEL (ppm)                        | 0.03 ppm   |

# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|                       |                              |  |
|-----------------------|------------------------------|--|
| Northwest Territories | OEL TWA (mg/m <sup>3</sup> ) | 0.09 mg/m <sup>3</sup>   |
| Northwest Territories | OEL TWA (ppm)                | 0.01 ppm   |
| Ontario               | OEL Ceiling (ppm)            | 0.02 ppm (designated substances regulation)  |
| Ontario               | OEL TWA (ppm)                | 0.005 ppm (applies to workplaces to which the designated substances regulation does not apply) |
| Prince Edward Island  | OEL TWA (ppm)                | 0.005 ppm  |
| Québec                | VEMP (mg/m <sup>3</sup> )    | 0.045 mg/m <sup>3</sup>  |
| Québec                | VEMP (ppm)                   | 0.005 ppm  |
| Saskatchewan          | OEL STEL (ppm)               | 0.015 ppm  |
| Saskatchewan          | OEL TWA (ppm)                | 0.005 ppm  |

### 1,4-Diazabicyclo[2.2.2]octane (280-57-9)

|         |                              |                       |
|---------|------------------------------|-----------------------|
| Ontario | OEL TWA (mg/m <sup>3</sup> ) | 4.6 mg/m <sup>3</sup> |
| Ontario | OEL TWA (ppm)                | 1 ppm                 |

### Exposure Controls

**Appropriate Engineering Controls:** Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Gas detectors should be used when flammable gases/vapours may be released.

**Personal Protective Equipment:** Protective goggles. Gloves. Protective clothing. Full protective flameproof clothing. Face shield. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical goggles or safety glasses. Face shield.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

**Thermal Hazard Protection:** Wear suitable protective clothing.

**Environmental Exposure Controls:** Do not allow the product to be released into the environment.

**Consumer Exposure Controls:** Do not eat, drink or smoke during use

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

|  |                         |
|--|-------------------------|
| Physical State                             | : Liquid                |
| Appearance                                 | : Viscous white         |
| Odor                                       | : Petroleum distillates |
| Odor Threshold                             | : Not available         |
| pH   | : Not available         |
| Relative Evaporation Rate (butylacetate=1) | : Not available         |
| Melting Point                              | : Not available         |
| Freezing Point                             | : Not available         |
| Boiling Point                              | : Not available         |
| Flash Point                                | : 41 °C (105.8 °F)      |
| Auto-ignition Temperature                  | : Not available         |
| Decomposition Temperature                  | : Not available         |
| Flammability (solid, gas)                  | : Not available         |
| Lower Flammable Limit                      | : Not available         |
| Upper Flammable Limit                      | : Not available         |

# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |   |
|--|---|
| <b>Vapor Pressure</b>                                    | : Not available   |
| <b>Relative Vapor Density at 20 °C</b>                   | : Not available   |
| <b>Relative Density</b>                                  | : Not available   |
| <b>Specific Gravity</b>                                  | : 1.25  |
| <b>Solubility</b>  | : Not available   |
| <b>Partition coefficient: n-octanol/water</b>            | : Not available   |
| <b>Viscosity</b>   | : Not available   |
| <b>Explosion Data – Sensitivity to Mechanical Impact</b> | : Not expected to present an explosion hazard due to mechanical impact. |
| <b>Explosion Data – Sensitivity to Static Discharge</b>  | : Not expected to present an explosion hazard due to static discharge.  |

### SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Hazardous reactions will not occur under normal conditions.

**Chemical Stability:** Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials. Open flame. Overheating. Heat. Sparks.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers.

**Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>). May release flammable gases. Oxides of tin. Hydrocarbons.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### Information on Toxicological Effects - Product

**Acute Toxicity:** Toxic if inhaled.

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Causes skin irritation.

**Serious Eye Damage/Irritation:** Causes serious eye irritation.

**Respiratory or Skin Sensitization:** May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** May cause genetic defects.

**Teratogenicity:** Not available

**Carcinogenicity:** May cause cancer.

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** May damage fertility or the unborn child.

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** May cause cancer by inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Toxic if inhaled.

**Symptoms/Injuries After Skin Contact:** Causes skin irritation. May cause an allergic skin reaction.

**Symptoms/Injuries After Eye Contact:** Causes serious eye irritation.

**Symptoms/Injuries After Ingestion:** May be fatal if swallowed and enters airways.

**Chronic Symptoms:** None expected under normal conditions of use.

#### Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

|  |               |
|--|---------------|
| <b>Quartz (14808-60-7)</b>                       |               |
| LD50 Oral Rat                                    | > 5000 mg/kg  |
| <b>2,6-Di-tert-butyl-p-cresol (128-37-0)</b>     |               |
| LD50 Oral Rat                                    | 890 mg/kg     |
| <b>Aluminum oxide (1344-28-1)</b>                |               |
| LD50 Oral Rat                                    | > 15900 mg/kg |
| LC50 Inhalation Rat (mg/l)                       | > 2.3 mg/l/4h |
| <b>Aluminum hydroxide (Al(OH)3) (21645-51-2)</b> |               |
| LD50 Oral Rat                                    | > 5000 mg/kg  |

# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|   |                                  |
|---|----------------------------------|
| <b>Dibutyltin dilaurate (77-58-7)</b>                               |                                  |
| LD50 Oral Rat   | 2071 mg/kg                       |
| LD50 Dermal Rat   | > 2000 mg/kg                     |
| LD50 Dermal Rabbit  | 630 mg/kg                        |
| <b>Toluene-2,4-diisocyanate (584-84-9)</b>                          |                                  |
| LD50 Oral Rat   | 3060 - 4130 mg/kg                |
| LC50 Inhalation Rat (ppm)   | 14 ppm/4h                        |
| <b>Bis(2-ethylhexyl) adipate (103-23-1)</b>                         |                                  |
| LD50 Oral Rat   | 5600 mg/kg                       |
| LD50 Dermal Rabbit  | 8410 mg/kg                       |
| <b>Dipropylene glycol (25265-71-8)</b>                              |                                  |
| LD50 Oral Rat   | 13300 mg/kg                      |
| LD50 Dermal Rabbit  | > 20 ml/kg                       |
| <b>Titanium dioxide (13463-67-7)</b>                                |                                  |
| LD50 Oral Rat   | > 10000 mg/kg                    |
| <b>Naphtha, petroleum, hydrotreated heavy (64742-48-9)</b>          |                                  |
| LD50 Oral Rat   | > 5000 mg/kg                     |
| LD50 Dermal Rabbit  | > 3160 mg/kg                     |
| <b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b> |                                  |
| LD50 Oral Rat   | 2615 mg/kg                       |
| <b>Isophorone diisocyanate (4098-71-9)</b>                          |                                  |
| LD50 Oral Rat   | 1270 mg/kg                       |
| LD50 Dermal Rabbit  | 4780 mg/kg                       |
| LC50 Inhalation Rat (mg/l)  | 0.135 mg/l/4h                    |
| <b>Silicic acid, aluminum sodium salt (1344-00-9)</b>               |                                  |
| LD50 Oral Rat   | 5000 mg/kg                       |
| LD50 Dermal Rabbit  | > 2000 mg/kg                     |
| LC50 Inhalation Rat (mg/l)  | > 18.3 mg/l (Exposure time: 1 h) |
| ATE (oral)  | 5000.000 mg/kg body weight       |
| <b>1,4-Diazabicyclo[2.2.2]octane (280-57-9)</b>                     |                                  |
| LD50 Oral Rat   | 1700 mg/kg                       |
| LD50 Dermal Rabbit  | 3200 mg/kg                       |
| <b>Quartz (14808-60-7)</b>  |                                  |
| IARC Group  | 1                                |
| National Toxicity Program (NTP) Status                              | Known Human Carcinogens.         |
| <b>2,6-Di-tert-butyl-p-cresol (128-37-0)</b>                        |                                  |
| IARC Group  | 3                                |
| <b>Silica gel, precipitated, crystalline free (112926-00-8)</b>     |                                  |
| IARC Group  | 3                                |
| <b>Toluene-2,4-diisocyanate (584-84-9)</b>                          |                                  |
| IARC Group  | 2B                               |
| <b>Toluene 2,6-diisocyanate (91-08-7)</b>                           |                                  |
| IARC Group  | 2B                               |
| <b>Bis(2-ethylhexyl) adipate (103-23-1)</b>                         |                                  |
| IARC Group  | 3                                |
| National Toxicity Program (NTP) Status                              | Evidence of Carcinogenicity.     |

# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |  |
|--|--|
| <b>Talc (14807-96-6)</b>               |  |
| IARC Group                             | 3  |
| National Toxicity Program (NTP) Status | Evidence of Carcinogenicity, Twelfth Report - Items under consideration. |
| <b>Titanium dioxide (13463-67-7)</b>   |  |
| IARC Group                             | 2B   |

## SECTION 12: ECOLOGICAL INFORMATION

### Toxicity

**Ecology - General:** Harmful to aquatic life with long lasting effects.

|   |  |
|---|--|
| <b>2,6-Di-tert-butyl-p-cresol (128-37-0)</b>                        |  |
| EC50 Other Aquatic Organisms 1                                      | 6 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata)              |
| EC50 Other Aquatic Organisms 2                                      | 0.43 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)                   |
| <b>Aluminum oxide (1344-28-1)</b>                                   |  |
| LC50 Fish 1   | 14.6 mg/l  |
| EC50 Daphnia 1  | 38.2 mg/l  |
| NOEC (acute)  | > 50 mg/l  |
| <b>Bis(2-ethylhexyl) adipate (103-23-1)</b>                         |  |
| LC50 Fish 1   | 0.48 - 0.85 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])       |
| EC50 Daphnia 1  | > 1.6 mg/l (Exposure time: 48 h - Species: Daphnia magna)                            |
| EC50 Other Aquatic Organisms 1                                      | > 500 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)                  |
| LC 50 Fish 2  | 0.48 - 0.85 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])       |
| <b>Talc (14807-96-6)</b>  |  |
| LC50 Fish 1   | > 100 g/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])           |
| <b>Naphtha, petroleum, hydrotreated heavy (64742-48-9)</b>          |  |
| LC50 Fish 1   | 2200 mg/l (Exposure time: 96 h - Species: Pimephales promelas)                       |
| <b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b> |  |
| LC50 Fish 1   | 0.97 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])              |
| <b>Isophorone diisocyanate (4098-71-9)</b>                          |  |
| EC50 Other Aquatic Organisms 1                                      | 118.7 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)                  |
| <b>Silicic acid, aluminum sodium salt (1344-00-9)</b>               |  |
| LC50 Fish 1   | 1800 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])           |
| EC50 Daphnia 1  | 1000 - 1800 mg/l (Exposure time: 48 h - Species: Daphnia magna)                      |
| EC50 Other Aquatic Organisms 1                                      | 18 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)                     |
| LC 50 Fish 2  | 3200 - 5600 mg/l (Exposure time: 96 h - Species: Oryzias latipes [semi-static])      |
| <b>1,4-Diazabicyclo[2.2.2]octane (280-57-9)</b>                     |  |
| LC50 Fish 1   | 1510 - 1980 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| <b>Persistence and Degradability</b> Not available                  |  |
| <b>Bioaccumulative Potential</b>                                    |  |
| <b>2,6-Di-tert-butyl-p-cresol (128-37-0)</b>                        |  |
| BCF fish 1  | 230 - 2500   |
| Log Pow   | 4.17   |
| <b>Bis(2-ethylhexyl) adipate (103-23-1)</b>                         |  |
| BCF fish 1  | 27   |
| Log Pow   | 8.114  |
| <b>Talc (14807-96-6)</b>  |  |
| BCF fish 1  | (no known bioaccumulation)   |

# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|   |                 |
|---|-----------------|
| <b>Dipropylene glycol (25265-71-8)</b>                              |                 |
| BCF fish 1  | 0.3 (0.3 - 1.4) |
| <b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b> |                 |
| Log Pow   | 0.37 (at 25 °C) |

**Mobility in Soil** Not available

### Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, and international regulations.

**Additional Information:** Handle empty containers with care because residual vapors are flammable.

**Ecology – Waste Materials:** Avoid release to the environment. Hazardous waste due to toxicity.

## SECTION 14: TRANSPORT INFORMATION

### 14.1 In Accordance with DOT

**Proper Shipping Name** : Not regulated for non-bulk packaging of <119 gallons (DOT 49 CFR 173.150(f))  
**Hazard Class** :  
**Identification Number** :  
**Label Codes** :  
**Packing Group** :  
**ERG Number** :

### 14.2 In Accordance with IMDG

**Proper Shipping Name** : Paint  
**Hazard Class** : 3  
**Identification Number** : UN1263  
**Packing Group** : III  
**Label Codes** : 3  
**EmS-No. (Fire)** : F-E  
**EmS-No. (Spillage)** : S-E  
**MFAG Number** : 127;128



### 14.3 In Accordance with IATA

**Proper Shipping Name** : Paint  
**Packing Group** : III  
**Identification Number** : UN1263  
**Hazard Class** : 3  
**Label Codes** : 3  
**ERG Code (IATA)** : 3L



### 14.4 In Accordance with TDG

**Proper Shipping Name** : Not regulated for non-bulk packaging of <119 gallons (DOT 49 CFR 173.150(f))  
**Packing Group** : I  
**Hazard Class** : 3  
**Identification Number** : UN1263  
**Label Codes** : 3

## SECTION 15: REGULATORY INFORMATION

### US Federal Regulations

|                                     |   |
|-------------------------------------|---|
| White-Knight® Dark Gray             |   |
| SARA Section 311/312 Hazard Classes | Fire hazard<br>Delayed (chronic) health hazard<br>Immediate (acute) health hazard |

# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |                       |
|--|-----------------------|
| <b>Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester (82919-37-7)</b> |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |
| <b>Quartz (14808-60-7)</b>   |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |
| <b>2,6-Di-tert-butyl-p-cresol (128-37-0)</b>   |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |
| <b>Aluminum oxide (1344-28-1)</b>  |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |
| Listed on SARA Section 313 (Specific toxic chemical listings)                          |                       |
| <b>SARA Section 313 - Emission Reporting</b>   | 1.0 % (fibrous forms) |
| <b>Aluminum hydroxide (Al(OH)3) (21645-51-2)</b>                                       |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |
| <b>Limestone (1317-65-3)</b>   |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |
| <b>Soybean lecithin (8002-43-5)</b>  |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |
| <b>Dibutyltin dilaurate (77-58-7)</b>  |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |
| <b>Toluene-2,4-diisocyanate (584-84-9)</b>   |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |
| Listed on SARA Section 302 (Specific toxic chemical listings)                          |                       |
| Listed on SARA Section 313 (Specific toxic chemical listings)                          |                       |
| <b>SARA Section 302 Threshold Planning Quantity (TPQ)</b>                              | 500                   |
| <b>SARA Section 313 - Emission Reporting</b>   | 0.1 %                 |
| <b>Toluene 2,6-diisocyanate (91-08-7)</b>  |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |
| Listed on SARA Section 302 (Specific toxic chemical listings)                          |                       |
| Listed on SARA Section 313 (Specific toxic chemical listings)                          |                       |
| <b>SARA Section 302 Threshold Planning Quantity (TPQ)</b>                              | 100                   |
| <b>SARA Section 313 - Emission Reporting</b>   | 0.1 %                 |
| <b>Bis(2-ethylhexyl) adipate (103-23-1)</b>  |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |
| <b>Talc (14807-96-6)</b>   |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |
| <b>Dipropylene glycol (25265-71-8)</b>   |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |
| <b>Magnesium carbonate (546-93-0)</b>  |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |
| <b>Titanium dioxide (13463-67-7)</b>   |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |
| <b>Naphtha, petroleum, hydrotreated heavy (64742-48-9)</b>                             |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |
| <b>Polypropylene glycol (25322-69-4)</b>   |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |
| <b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>                    |                       |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory              |                       |

# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |  |
|--|--|
| <b>Isophorone diisocyanate (4098-71-9)</b>   |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |  |
| Listed on SARA Section 302 (Specific toxic chemical listings)  |  |
| Listed on SARA Section 313 (Specific toxic chemical listings)  |  |
| <b>SARA Section 302 Threshold Planning Quantity (TPQ)</b>  | 500  |
| <b>SARA Section 313 - Emission Reporting</b>   | 1.0 %  |
| <b>Propane, oxybis(methoxy- (111109-77-4)</b>  |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |  |
| <b>EPA TSCA Regulatory Flag</b>  | S - S - indicates a substance that is identified in a proposed or final Significant New Uses Rule. |
| <b>Silicic acid, aluminum sodium salt (1344-00-9)</b>  |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |  |
| <b>1,4-Diazabicyclo[2.2.2]octane (280-57-9)</b>  |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |  |
| <b>Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]- (104810-47-1)</b> |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |  |
| <b>Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- (104810-48-2)</b>   |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory  |  |
| <b>US State Regulations</b>  |  |
| <b>Quartz (14808-60-7)</b>   |  |
| <b>U.S. - California - Proposition 65 - Carcinogens List</b>   | WARNING: This product contains chemicals known to the State of California to cause cancer.         |
| <b>Titanium dioxide (13463-67-7)</b>   |  |
| <b>U.S. - California - Proposition 65 - Carcinogens List</b>   | WARNING: This product contains chemicals known to the State of California to cause cancer.         |
| <b>Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester (82919-37-7)</b>   |  |
| U.S. - Texas - Effects Screening Levels - Long Term  |  |
| U.S. - Texas - Effects Screening Levels - Short Term   |  |
| <b>Quartz (14808-60-7)</b>   |  |
| RTK - U.S. - Massachusetts - Right To Know List  |  |
| RTK - U.S. - New Jersey - Right to Know Hazardous Substance List   |  |
| RTK - U.S. - Pennsylvania - RTK (Right to Know) List   |  |
| <b>2,6-Di-tert-butyl-p-cresol (128-37-0)</b>   |  |
| RTK - U.S. - Massachusetts - Right To Know List  |  |
| RTK - U.S. - New Jersey - Right to Know Hazardous Substance List   |  |
| RTK - U.S. - Pennsylvania - RTK (Right to Know) List   |  |
| <b>Aluminum oxide (1344-28-1)</b>  |  |
| RTK - U.S. - Massachusetts - Right To Know List  |  |
| RTK - U.S. - New Jersey - Right to Know Hazardous Substance List   |  |
| RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  |  |
| RTK - U.S. - Pennsylvania - RTK (Right to Know) List   |  |
| <b>Limestone (1317-65-3)</b>   |  |
| RTK - U.S. - Massachusetts - Right To Know List  |  |
| RTK - U.S. - New Jersey - Right to Know Hazardous Substance List   |  |
| RTK - U.S. - Pennsylvania - RTK (Right to Know) List   |  |
| <b>Silica gel, precipitated, crystalline free (112926-00-8)</b>  |  |
| RTK - U.S. - Massachusetts - Right To Know List  |  |



# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

### **Toluene-2,4-diisocyanate (584-84-9)**

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

RTK - U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

### **Toluene 2,6-diisocyanate (91-08-7)**

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

### **Bis(2-ethylhexyl) adipate (103-23-1)**

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

### **Talc (14807-96-6)**

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

### **Dipropylene glycol (25265-71-8)**

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

### **Magnesium carbonate (546-93-0)**

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

### **Titanium dioxide (13463-67-7)**

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

### **Isophorone diisocyanate (4098-71-9)**

RTK - U.S. - Massachusetts - Right To Know List

RTK - U.S. - New Jersey - Right to Know Hazardous Substance List

RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

RTK - U.S. - Pennsylvania - RTK (Right to Know) List

### **Canadian Regulations**

#### **White-Knight® Dark Gray**

WHMIS Classification

Class B Division 2 - Flammable Liquid

Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects

Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Class D Division 2 Subdivision B - Toxic material causing other toxic effects



#### **Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl ester (82919-37-7)**

Listed on the Canadian DSL (Domestic Substances List) inventory.

# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|   |   |
|---|---|
| <b>Quartz (14808-60-7)</b>  |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.<br>Listed on the Canadian Ingredient Disclosure List |   |
| WHMIS Classification  | Class D Division 2 Subdivision A - Very toxic material causing other toxic effects  |
| <b>2,6-Di-tert-butyl-p-cresol (128-37-0)</b>  |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.<br>Listed on the Canadian Ingredient Disclosure List |   |
| WHMIS Classification  | Uncontrolled product according to WHMIS classification criteria   |
| <b>Aluminum oxide (1344-28-1)</b>   |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.<br>Listed on the Canadian Ingredient Disclosure List |   |
| WHMIS Classification  | Uncontrolled product according to WHMIS classification criteria   |
| <b>Aluminum hydroxide (Al(OH)3) (21645-51-2)</b>  |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.  |   |
| WHMIS Classification  | Uncontrolled product according to WHMIS classification criteria   |
| <b>Limestone (1317-65-3)</b>  |   |
| Listed on Non-Domestic Substances List (NDSL)   |   |
| WHMIS Classification  | Class D Division 2 Subdivision A - Very toxic material causing other toxic effects  |
| <b>Silica gel, precipitated, crystalline free (112926-00-8)</b>   |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.  |   |
| WHMIS Classification  | Uncontrolled product according to WHMIS classification criteria   |
| <b>Soybean lecithin (8002-43-5)</b>   |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.  |   |
| <b>Dibutyltin dilaurate (77-58-7)</b>   |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.<br>Listed on the Canadian Ingredient Disclosure List |   |
| WHMIS Classification  | Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects<br>Class D Division 2 Subdivision B - Toxic material causing other toxic effects  |
| <b>Toluene-2,4-diisocyanate (584-84-9)</b>  |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.<br>Listed on the Canadian Ingredient Disclosure List |   |
| WHMIS Classification  | Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects<br>Class D Division 2 Subdivision A - Very toxic material causing other toxic effects<br>Class D Division 2 Subdivision B - Toxic material causing other toxic effects |
| <b>Toluene 2,6-diisocyanate (91-08-7)</b>   |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.<br>Listed on the Canadian Ingredient Disclosure List |   |
| WHMIS Classification  | Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects<br>Class D Division 2 Subdivision A - Very toxic material causing other toxic effects<br>Class D Division 2 Subdivision B - Toxic material causing other toxic effects |
| <b>Bis(2-ethylhexyl) adipate (103-23-1)</b>   |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.<br>Listed on the Canadian Ingredient Disclosure List |   |
| <b>Talc (14807-96-6)</b>  |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.  |   |
| WHMIS Classification  | Class D Division 2 Subdivision A - Very toxic material causing other toxic effects  |
| <b>Dipropylene glycol (25265-71-8)</b>  |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.  |   |

# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |   |
|--|---|
| <b>Magnesium carbonate (546-93-0)</b>  |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.   |   |
| WHMIS Classification   | Uncontrolled product according to WHMIS classification criteria   |
| <b>Titanium dioxide (13463-67-7)</b>   |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.   |   |
| WHMIS Classification   | Class D Division 2 Subdivision A - Very toxic material causing other toxic effects  |
| <b>Naphtha, petroleum, hydrotreated heavy (64742-48-9)</b>   |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.   |   |
| WHMIS Classification   | Class B Division 3 - Combustible Liquid<br>Class D Division 2 Subdivision A - Very toxic material causing other toxic effects<br>Class D Division 2 Subdivision B - Toxic material causing other toxic effects  |
| <b>Polypropylene glycol (25322-69-4)</b>   |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.   |   |
| <b>Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (41556-26-7)</b>  |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.   |   |
| <b>Isophorone diisocyanate (4098-71-9)</b>   |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.<br>Listed on the Canadian Ingredient Disclosure List  |   |
| WHMIS Classification   | Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects<br>Class D Division 2 Subdivision A - Very toxic material causing other toxic effects<br>Class D Division 2 Subdivision B - Toxic material causing other toxic effects |
| <b>Propane, oxybis(methoxy- (111109-77-4)</b>  |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.   |   |
| <b>Silicic acid, aluminum sodium salt (1344-00-9)</b>  |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.   |   |
| WHMIS Classification   | Uncontrolled product according to WHMIS classification criteria   |
| <b>1,4-Diazabicyclo[2.2.2]octane (280-57-9)</b>  |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.<br>Listed on the Canadian Ingredient Disclosure List  |   |
| <b>Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]- (104810-47-1)</b> |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.   |   |
| <b>Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy- (104810-48-2)</b>   |   |
| Listed on the Canadian DSL (Domestic Substances List) inventory.   |   |

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

### SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision date** : 10/06/2014  
**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

#### Party Responsible for the Preparation of This Document

Garland Canada, Inc.  
209 Carrier Drive  
Toronto, Ontario M9W 5Y8  
416-747-7995  
[tania@garlandcanada.com](mailto:tania@garlandcanada.com)

# White-Knight® Dark Gray

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

*This information is based on our knowledge as of the Revision Date and is intended to describe the product only for the purposes of health, safety, and environmental requirements as of the Revision Date. It should not therefore be construed as guaranteeing any specific property of the product nor as providing any warranty, expressed or implied. The user assumes all responsibility, liability, risk of loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use, or disposal of the product.*

North America GHS US 2012 & WHMIS